

1.3 Gbps Wi-Fi 5 Mesh Gigabit Router Dual-band 802.11ac Wave 2 57MM-WR04



The 57MM-WR04 is a Wi-Fi 5 Gigabit meshing router offering speeds up to 400 Mbps over 2.4 GHz and 867 Mbps over 5 GHz Wi-Fi channels. With the 6 x omnidirectional antennas, the WR04 provides a strong and consistently high throughput Wi-Fi signal throughout your home or office. In addition, you can easily build your home or office network using MESH technology while managing and supporting the system via the free cloud-based app.

Ruijie

Features and Benefits

- » Dual-band 802.11ac (Wi-Fi 5) Wave 2 support speeds up to 1267 Mbps
- » MESH technology for seamless roaming between units
- » Simple setup, parental control and network management at your fingertips with the Reyee Router app
- » One 10/100/1000 Base-T WAN port, three 10/100/1000 Base-T LAN ports
- » Dual-band integration and the MU-MIMO technology offer low interference and fast-speed internet to up to 64 terminals simultaneously (recommended users 32).
- » The operating mode can also be set as a Wi-Fi repeater, meaning any Wi-Fi network can be received and transmitted.



1.3 Gbps Wi-Fi 5 Mesh Gigabit Router Dual-band 802.11ac Wave 2

57MM-WR04



For the Best

57MM-WR04 Specifications

Hardware Specifications	
Dimensions (WxDxH)	220 mm x 140 mm x 36 mm (8.67 in. x 5.51 in. x 1.42 in. antennas not included)
Weight	0.55 kg (packages not included)
Wi-Fi Standards	Wi-Fi 5 (802.11ac)
MIMO	2.4 GHz, 4x4, MU-MIMO 5 GHz, 4x4, MU-MIMO
Max. Wi-Fi Speed	2.4 GHz: 800 Mbps 5 GHz: 2402 Mbps
Channel Width	2.4 GHz: Auto/20/40 MHz 5 GHz: Auto/20/40/80 MHz
Antennas	6
Antennas Type	External Omnidirectional
Antenna Gain	2.4 GHz: 5 dBi 5 GHz: 6 dBi
WAN Port	1x10/100/1000 Base-T Port
LAN Ports	3x10/100/1000 Base-T Ports
Recommended Users	32
Max. Users	96
Power Supply	DC 12V/1.5A
Power Consumption	≤15W
Operation Frequency Bands	802.11b/g/n: 2.400 GHz to 2.483 GHz 802.11a/n/ac: 5.150 GHz to 5.350 GHz 802.11a/n/ac: 5.470 GHz to 5.725 GHz , 5.725 GHz to 5.850 GHz country-specific restrictions apply
Transmit Power	Regular: CE EIRP: ≤20 dBm (2.4 GHz) ≤27 dBm (5 GHz)
Operating Temperature	0 °C to +45 °C (32 °F to 113 °F)
Operating Humidity	5% to 95% Noncondensing
Certifications	CE,RoHS
Wireless	
OFDMA	No
MU-MIMO	Yes
BSS Coloring	No
Maximum Number of SSIDs	6
SSID Hiding	Yes
Band Steering	Yes
Guest Wi-Fi	Yes
WPA/WPA2	Yes

WPA3	No
Roaming	Layer 2 Roaming
Blacklist	Yes
Reyee Mesh	Yes
Mesh Pairing by Hardware	Yes
Mesh Pairing by Mesh Button	Yes
Mesh Pairing by Eweb	Yes
Recommended Hop Count	≤2
Wi-Fi Optimization	Yes
QoS (WMM)	Yes
WPS	No
Transmission Power Adjustment	Yes
DFS	Yes
Hardware	
CPU	MT7621
Flash	16 MB
RAM/SDRAM	128MB
Color	Black
System LED Indicator	Yes
Reyee Mesh LED Indicator	No
Reyee Mesh Button	Yes
Power Button	No
Reset Button	Yes
DC Connector Dimensions	5.5 mm x 2.1 mm x 9 mm (0.22 in. x 0.08 in. x 0.35 in. antennas not included)
WAN	
Static IP	Yes
DHCP	Yes
PPPoE	Yes
Learning PPPoE Account & Password	Yes
VLAN Tagging	Yes
LAN	
DHCP Server	Yes
Client List	Yes
Static IP Assignment	Yes
Port-Based Flow Control	Yes
Features	
IPv6	Yes
DDNS	Yes
IPTV	Yes
Alarm	Yes
Diagnosis	Yes
UPnP	Yes
ARP Binding	Yes
Port Mapping	Yes
DMZ Host	Yes

1.3 Gbps Wi-Fi 5 Mesh Gigabit Router Dual-band 802.11ac Wave 2 57MM-WR04



For the Best

Rate Limitation of Terminals	Yes
Hardware Acceleration	Yes
MAC Address Cloning	Yes
Cloud Management	Yes
Repeater Mode	Yes
WISP Mode	Yes
Security	
PPTP VPN Server	No
PPTP VPN Client	Yes
L2TP VPN Client	No
Parental Control	Yes
Protect TCP Flood Attacks	Yes
Protect ICMP Attacks	No
Protect UDP Flood Attacks	No
System	
Default Access/Password	192.168.110.1 No Password Required by Default
URL Access	Yes
Local Upgrade	Yes
Online Upgrade	Yes
APP Upgrade	Yes
Syslog	No
Backup	Yes
Factory Reset	Yes
Language	Chinese English Vietnamese Indonesian Thai Arabic Traditional Chinese Spanish Russian
Package Contents	
Wireless Router	1
Power Adapter	1
Quick Start Guide	1
Cat5E UTP Cable	1