

PRODUCT-DETAILS

LFH-SPL32/10M

LOW FIR.HAZ.LIQ.TIGHT NC32 10MT BLK



Product image
not available

General Information

Extended Product Type	LFH-SPL32/10M
Product ID	7TCA296030R0407
EAN	5020963800740
Catalog Description	LOW FIR.HAZ.LIQ.TIGHT NC32 10MT BLK
Long Description	Liquid Tight, Low Fire Hazard, Medium Flexibility Conduit, 1 Inch, Nominal Conduit Size 32mm, Outside Diameter 34mm, Inside Diameter 28.1mm, Static Bend Radius 145mm, Galvanised Steel Core with Low Fire Hazard Jacket, Reel Length 10 Meters, Black

Additional Information

Application	Rail, Buildings - Where Low Smoke & Toxicity is a Primary Concern
Product Type	Low Fire Hazard Conduit

Ordering

EAN	5020963800740
UPC	786210289731
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	10 m
----------------------------	------

Technical

Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Low Fire Hazard Jacket

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	LFH-SPL32/10M
Instructions and Manuals	LFH-SPL32/10M
Declaration of Conformity - CE	9AKK107492A9618
RoHS Information	9AKK107992A8994
REACH Declaration	9AKK107992A8994

Classifications

UNSPSC	39131706
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available