



1711343-2

**AMP-TWIST SL-Series Modular Jack, category 6, 4 pair, for F/UTP cables, side exit, without dust cover**

## Body Features

110 Block Material Polycarbonate

## Configuration Features

Keyed No  
Number of Positions 8  
Port Configuration Single  
Wiring Pattern Universal

## Contact Features

Contact Base Material Beryllium copper  
Contact Mating Area Plating Material Gold  
Contact Mating Area Plating Thickness 50.00 µin | 1.27 µm

## Dimensions

Cable Diameter (Max) 9.0 mm | 0.4 in  
Conductor Outside Diameter 0.0629 in | 1.6 mm  
Height 20.500 mm | 0.807 in  
PCB Thickness (Recommended) 1.600 mm | 0.063 in  
Solid Wire Range 24 - 22 AWG  
Stranded Wire Range 26 - 24 AWG

## Housing Features

Housing Color Gray  
Housing Material Zamak 5

## Other

Comment Side Exit

## Packaging Features

Packaging Method Box | Tray/Box  
Packaging Quantity 12

1711343-2

## Product Availability

Region Australia/New Zealand | EMEA

## Product Type Features

Product Type	Connector - Modular
Performance Category	Category 6
Shielded	Yes
System	AMP NETCONNECT   AMP-TWIST Series   SL Series
Applies To	Panel
Connector Style	Jack
Connector Type	Connector Assembly
Dust Cover	Without
Jack Type	RJ45

## Termination Features

Termination Method to Wire/Cable	Insulation Displacement Crimp (IDC)
Termination Style	SL Termination Tool

## Regulatory Compliance/Certifications

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant