


PVC / SWA / PVC CONTROL CABLES



AUSTRALIA PACIFIC ELECTRIC CABLES



PVC Insulated, Steel Wire Armoured,
PVC Sheathed Multicore plus insulated earth
0.6/1kv to AS/NZS 5000.1

Conductor: Annealed bare copper stranded

Insulation: V90 PVC

Sheath: 3V90 PVC

Armoured: Galvanised steel wire armoured

Standard Colours

Core: White with Black numbers

Inner Sheath: Black

Outer Sheath: Black

Nominal Conductor area cores & earth mm ²	Number of Cores	Nominal OD of Insulation mm	Nominal OD of Inner Sheath mm	Nominal OD after SWA mm	Thickness of Outer Sheath mm	Nominal Overall Diameter mm	Nominal Weight kg/100m	Product Code
*Please note; Tolerance of approx. $\pm 10\%$ is applicable								
1.5 (7/0.50)	2 + 1E	3.1	8.8	10.6	1.8	14.2	39.7	VCS105E02B5K1
1.5 (7/0.50)	4 + 1E	3.1	10.5	13.0	1.8	16.6	59.2	VCS105E04B4K1
1.5 (7/0.50)	6 + 1E	3.1	11.4	13.9	1.8	17.5	67.5	VCS105E06B5K1
1.5 (7/0.50)	8 + 1E	3.1	14.5	17.0	1.8	20.6	84.0	VCS105E08B5K1
1.5 (7/0.50)	10 + 1E	3.1	15.0	17.5	1.8	21.1	90.2	VCS105E10B5K1
1.5 (7/0.50)	12 + 1E	3.1	15.8	19.0	1.8	22.6	112.0	VCS105E12B5K1
1.5 (7/0.50)	15 + 1E	3.1	16.7	19.9	1.8	23.5	122.6	VCS105E15B5K1
1.5 (7/0.50)	16 + 1E	3.1	17.3	20.5	1.8	24.1	127.7	VCS105E16B5K1
1.5 (7/0.50)	20 + 1E	3.1	18.5	21.7	1.8	25.3	142.0	VCS105E20B5K1
1.5 (7/0.50)	25 + 1E	3.1	21.2	24.4	1.9	28.2	166.3	VCS105E25B5K1
1.5 (7/0.50)	30 + 1E	3.1	22.9	26.1	1.9	29.9	185.0	VCS105E30B5K1
2.5 (7/0.67)	2 + 1E	3.6	10	12.5	1.8	16.1	56.8	VCS205E02B5K1
2.5 (7/0.67)	4 + 1E	3.6	11.9	14.4	1.8	18.1	71.0	VCS205E04B5K1
2.5 (7/0.67)	5 + 1E	3.6	13	15.5	1.8	19.1	78.6	VCS205E05B5K1
2.5 (7/0.67)	6 + 1E	3.6	13	15.5	1.8	19.1	81.5	VCS205E06B5K1
2.5 (7/0.67)	8 + 1E	3.6	15.6	18.8	1.8	22.4	112.7	VCS205E08B5K1
2.5 (7/0.67)	10 + 1E	3.6	17.2	20.4	1.8	24	127.1	VCS205E10B5K1
2.5 (7/0.67)	12 + 1E	3.6	18.1	21.3	1.8	24.9	137.6	VCS205E12B5K1
2.5 (7/0.67)	15 + 1E	3.6	19.2	22.4	1.8	26	152.8	VCS205E15B5K1
2.5 (7/0.67)	20 + 1E	3.6	21.3	24.5	1.8	28.1	179.5	VCS205E20B5K1
2.5 (7/0.67)	25 + 1E	3.6	24.4	27.6	2	31.6	213.4	VCS205E25B5K1
2.5 (7/0.67)	30 + 1E	3.6	26.4	30.4	2	34.4	265.1	VCS205E30B5K1