

HyFlex® 11-630



CUT PROTECTION



M MEDIUM

MECHANICAL PROTECTION

STYLE #	CONSTRUCTION	LINER MATERIAL	COATING MATERIAL	CUFF STYLE	COLOUR	LENGTH MM	EN SIZE	PACKAGING
11-630 ★	Palm coated	NylonLycra® Kevlar® HPPECotton	Polyurethane	Elasticated cuff	Grey coating on grey liner	215 - 275	6, 7, 8, 9, 10, 11	12 pairs in a bag, 12 bags in a carton



Dexterity with superb cut resistance for optimal productivity

PRIMARY INDUSTRIES

- Automotive & Transportation
- Metal Fabrication
- Glass
- Machinery & Equipment
- Building & Construction
- Maintenance

IDEAL APPLICATIONS

- Glass manufacturing
- Aeronautics
- Assembly of white goods
- Plastics injection and moulding
- Assembling metal parts and components
- Handling sharp or irregular-edged metal parts




DESCRIPTION

- The liners of the HyFlex® 11-630 glove has a yarn structure that contains an optimal rate of HPPE. This offers high levels of cut resistance, for a safe use in controlling, handling and assembly applications involving contacts with sharp pieces.
- The Lycra® in the liners of the glove, as well as the polyurethane coating, provides excellent flexibility and fit.
- The specific formulation of the polyurethane dipping provides a secure grip on dry or slightly oily pieces.
- The PU formulation also increases abrasion resistance on the gloves' work surface.

FEATURED TECHNOLOGY

Kevlar®



CATEGORY II

Testing compliant to AS/NZS 2161

Ansell Limited

678 Victoria Street (Level 3) Richmond VIC 3121 Australia
Phone + 61 3 9270 7270 Fax + 61 3 9270 7300

Website: www.ansell.com E-mail: protection@ap.ansell.com

