

Data & Instrument

Screened Signal Cable



Application:

For connection of low voltage signal, audio and instrument equipment. Used where EMI screening is required

Benefits	
EMI Shielding	Tinned copper braid reduces the affect of electrical interference throughout the frequency spectrum
Extremely Flexible	Flexible conductor and braid stranding allow for high flexibility
Easy to Install	Flexible cable using class 5 conductors
Easy to Solder	Tinned copper conductors for easy adhesion
Marine Applications	Tinned copper conductors minimise corrosion in marine environments

Features	
✓	Copper braid with minimum coverage of 80% gives excellent EMI shielding
✓	V90-HT insulation for high temperature applications
✓	Oxygen free tinned copper for high conductivity soldered connections and corrosion protection
✓	Fine stranded conductors for high flexibility
✓	Highly flexible 5V90 PVC sheath for easy bending
✓	UV resistant black sheath provides extended outdoor life
✓	RoHS compliant to comply with European environmental requirements

Construction	
Conductor	Oxygen free tinned annealed copper wire, class 5
Insulation	V90-HT PVC
Screening	Oxygen free tinned annealed copper wire, minimum coverage 80%
Sheath	5V90 PVC
Colours	1 Core – Red 2 Core – Red & white, 3 Core – Red, blue & green 4 Core – Red, black, yellow & blue 6 Core – Black, blue, green, red, white & yellow

Ratings	
Temperature	-10°C to + 90°C
Voltage	ELV - 50V a.c. 120V ripple free d.c.
Applicable Standards	AS/NZS1125, AS/NZS3808, AS/NZS1660.5.6, IEC 60228, IEC 60332-1



Flexible Conductor:
Class 5



Oxygen Free, Tinned Copper
for Corrosion Resistance



Minimum Service
Temperature:
-10°C



Maximum Service
Temperature:
90°C



Impact Resistant



Abrasion Resistant



Chemical & Oil
Resistant



UV Resistant



Flame
Non-Propagation



Metre Marking



Minimum Recommended
Bend Radius Fixed 6 x OD

SYDNEY (Head Office)
102 Old Pittwater Road
Brookvale NSW 2100
Phone: 02 9938 5622
Fax: 02 9938 3973

BRISBANE
Unit 4/12 Selhurst St
Coopers Plain QLD 4108
Phone: 07 3344 1763
Fax: 07 3345 4076

MELBOURNE
9/24-26 Carrick Drive
Tullamarine VIC 3043
Phone: 03 9335 2600
Fax: 03 9330 3903

NEWCASTLE
64 Orlando Road
Lambton NSW 2299
Phone: 02 4956 2044
Fax: 02 4956 1983

WESTERN AUSTRALIA
1 Karratha St
Welshpool WA 6106
Phone: 08 9351 9966
Fax: 08 9356 2522



Data and Instrument - Collectively Screened

Bambach Item Code	No. of Cores x Conductor CSA mm ²	Conductor Stranding No. Strands/mm	Nom Ø mm	Weight kg/km
11320	1 x 0.5	16/0.20	4.0	24
15700	2 x 0.5	16/0.20	5.6	44
19280	3 x 0.5	16/0.20	5.6	60
22120	4 x 0.5	16/0.20	5.8	69
22550	6 x 0.5	16/0.20	7.3	81
11675	1 x 0.75	24/0.20	5.2	46
11955	1 x 1	32/0.20	5.4	50

Electrical Parameters

Bambach Item Code	Max. Conductor DC Resistance at 20°C	Capacitance Core – Core, 1kHz pF/m	Capacitance Core – Screen, 1kHz pF/m	Inductance Parallel Cores, 1kHz µH/m	L/R µH/Ω
11320	40.1	-	445	-	-
15700	40.1	183	-	0.63	7.9
19280	40.1	183	-	0.63	7.9
22120	40.1	183	-	0.63	7.9
22550	40.1	183	-	0.63	7.9
11675	26.7	-	320	-	-
11955	20.0	-	353	-	-