

OSP6AF Multi-Conductor - Category 6A Outside Plant F/UTP Cable



For more Information
please call

1-800-Belden1



General Description:

CAT6A (500 MHz), 4 Pair, F/UTP-Foil Shielded, Outdoor OSP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Patented X-Spline, Gel-Filled, UV resistant LLDPE Inner Jacket, Overall Beldfoil® Shield with Drain Wire, Ripcord, UV Resistance LLDPE Outer Jacket

Usage (Overall)

Suitable Applications: Outside Plant Cable, 10 Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, PoE, PoE+

Physical Characteristics (Overall)

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material
4	23	Solid	BC - Bare Copper

Total Number of Conductors: 8

Insulation

Insulation Material:

Insulation Material
Polyolefin

Inner Jacket

Inner Jacket Material:

Inner Jacket Material
LLDPE

Inner Jacket Ripcord: Yes

Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Coverage (%)	Dia. (mm)
Beldfoil(R)	Aluminum Foil / Polyester	100.000	6.985

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
26	7 x 34	Tinned Copper

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
LLDPE

Outer Jacket Diameter:

Nom. Dia. (mm)
9.144

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Separator Material: Patented X-Spline Center Member

Pair

Pair Color Code Chart:

Number	Color
1	White + Blue
2	White + Orange
3	White + Green
4	White + Brown

Mechanical Characteristics (Overall)

Storage Temperature Range: -40°C To +75°C

METRIC MEASUREMENT VERSION

OSP6AF Multi-Conductor - Category 6A Outside Plant F/UTP Cable

Installation Temperature Range:	-40°C To +60°C
Operating Temperature Range:	-40°C To +75°C
Non-UL Temperature Rating:	75C
Bulk Cable Weight:	72.922 Kg/Km
Max. Recommended Pulling Tension:	200.169 N
Min. Bend Radius/Minor Axis:	76.200 mm
Min. Bend/Installation:	95.250 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II):	Yes
IEEE Specification:	POE per 802.3af & POE+ per 802.3at-2009
EU CE Mark:	No
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	03/02/2016
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Telecommunications Standards:	Category 6A - TIA 568.C.2
ANSI Specification:	ANSI/TIA 568-C.2 Category 6A, ANSI/ICEA S-116-732-2013 Category6A, ANSI/NEMA WC-63.1 Category 6A
Other Specification:	Verified Channel/Category 6A, ANSI/ICEA S-56-434 Outdoor Use, ANSI/ICEA S-99-689 Broadband Outdoor Use

Applicable Patents:

Country

www.belden.com/p

Suitability

Suitability - Indoor:	No
Suitability - Outdoor:	Yes
Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	Yes
Suitability - Hazardous Locations:	No
Sunlight Resistance:	Yes
Oil Resistance:	No
Non-halogenated:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	10GX53F
Non-Plenum Number:	10GX52F

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

Capacitance (pF/m)

55.777

Maximum Capacitance Unbalance (pF/100 m):	45
---	----

Nominal Velocity of Propagation:

VP (%)

64.000

Maximum Delay:

Delay (ns/100 m)

538 @ 100MHz

Max. Delay Skew:

METRIC MEASUREMENT VERSION

OSP6AF Multi-Conductor - Category 6A Outside Plant F/UTP Cable

Delay Skew (ns/100 m)

45.000

Maximum Conductor DC Resistance:
DCR @ 20°C (Ohm/100 m)

8.200

Max. Operating Voltage - UL:
Voltage

300 V RMS

Maximum DCR Unbalanced:
DCR Unbalance @ 20°C (%)

3.000

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

Freq. (MHz)	Max. Attenuation (dB/100 m)	Min. PSNEXT (dB)	Min. PSACR (dB)	Min RL (dB)
1	2.100	72.3	70.2	20.000
4	3.800	63.3	59.5	23.000
8	5.300	58.8	53.4	24.500
10	5.900	57.3	51.4	25.000
16	7.500	54.2	46.8	25.000
20	8.400	52.8	44.4	25.000
25	9.400	51.3	42.0	24.300
31.25	10.500	49.9	39.4	23.600
62.5	15.000	45.4	30.4	21.500
100	19.100	42.3	23.2	20.100
200	27.600	37.8	11.2	18.700
250	31.100	36.3	5.3	18.000
300	34.300	35.1	0.9	17.500
350	37.200	34.1	N/A	17.000
400	40.100	33.3	N/A	16.600
450	42.700	32.5	N/A	16.200
500	45.300	31.8	N/A	15.900

Premise Cable Electrical Table 2:

Freq. (MHz)	Input (Unfitted) Imp. (Ohms)	Fitted Impedance	Min. ACRF (dB)	Min. PSACRF (dB)
1	105 ± 10	115 ± 15	67.8	64.8
4	100 ± 22	100 ± 7	55.8	52.8
8	100 ± 22	100 ± 7	49.7	46.7
10	100 ± 22	100 ± 7	47.8	44.8
16	100 ± 22	100 ± 7	43.7	40.7
20	100 ± 22	100 ± 7	41.8	38.8
25	100 ± 22	100 ± 7	39.8	36.8
31.25	100 ± 22	100 ± 7	37.9	34.9
62.5	100 ± 22	100 ± 7	31.9	28.9
100	100 ± 22	100 ± 7	27.8	24.8
200	100 ± 22	100 ± 7	21.8	18.8
250	100 ± 32	100 ± 7	19.8	16.8
300	100 ± 32	100 ± 7	18.3	15.3
350	100 ± 32	100 ± 7	16.9	13.9
400	100 ± 32	100 ± 7	15.8	12.8
450	100 ± 32	100 ± 7	14.7	11.7
500	100 ± 32	100 ± 7	13.8	10.8

Premise Cable Electrical Table 4:

Frequency (MHz)	Min. PSANEXT (dB)	Min. PSAACRF (dB)	Min. TCL (dB)	Min. ELTCTL (dB)
1.000	67.000	67.000	40.000	35.000
4.000	67.000	66.200	40.000	23.000
8.000	67.000	60.100	40.000	16.900
10.000	67.000	58.200	40.000	15.000
16.000	67.000	54.100	38.000	10.900
20.000	67.000	52.200	37.000	9.000
25.000	67.000	50.200	36.000	7.000
31.250	67.000	48.300	35.100	5.100
62.500	65.600	42.300	32.000	
100.000	62.500	38.200	30.000	
200.000	58.000	32.200	27.000	
250.000	56.500	30.200	26.000	

METRIC MEASUREMENT VERSION

OSP6AF Multi-Conductor - Category 6A Outside Plant F/UTP Cable

300.000	55.300	28.700	25.200	
350.000	54.300	27.300	24.600	
400.000	53.500	26.200	24.000	
450.000	52.700	25.100	23.500	
500.000	52.000	24.200	23.000	

Notes (Overall)

Notes: Print Includes Descending Footage / Meter Markings -40C Cold Bend Compliance Per UL1581, Water Penetration per GR 421-CORE para. 4.3.5.1. and per ANSI/ICEA S-107-704 Para. 8.2.1, ANSI/ ICEA S-99-689 Reference T/8-6 for Burial Reference T/8-36 Sag And Span Aerial

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
OSP6AF 0101000	1,000 FT	54.000 LB	BLACK		CAT6A 4PR F/UTP OSP REEL

Revision Number: 1 Revision Date: 08-22-2017

© 2017 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.