


FANCY ROUND HALOGEN GLOBES

- Input voltage: 240V AC
- Wattage: 18W & 28W
- Clear or frosted glass
- 30% more energy saving compared to incandescent
- Especially suitable for chandeliers and small fittings
- Can be used indoors & outdoors in a waterproof fitting
- Suitable for dimming



CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS		
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	LENGTH (mm)	DIAM (mm)	CARTON QTY
CLEAR								
CLAHAFR18WBCCL	18W F/R HALOGEN BC CLEAR	B22	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WBCCL	28W F/R HALOGEN BC CLEAR	B22	2800	370	28=40	72	Ø44	10/100
CLAHAFR18WESCL	18W F/R HALOGEN ES CLEAR	E27	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WESCL	28W F/R HALOGEN ES CLEAR	E27	2800	370	28=40	72	Ø44	10/100
CLAHAFR18WSBCCL	18W F/R HALOGEN SBC CLEAR	B15	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WSBCCL	28W F/R HALOGEN SBC CLEAR	B15	2800	370	28=40	72	Ø44	10/100
CLAHAFR18WSESCL	18W F/R HALOGEN SES CLEAR	E14	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WSESCL	28W F/R HALOGEN SES CLEAR	E14	2800	370	28=40	72	Ø44	10/100

CODE	DESCRIPTION	TECHNICAL DATA				DIMENSIONS		
		BASE	KELVIN (K)	LUMENS (LM)	WATT (W)	LENGTH (mm)	DIAM (mm)	CARTON QTY
FROSTED								
CLAHAFR18WBCFR	18W F/R HALOGEN BC FROSTED	B22	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WBCFR	28W F/R HALOGEN BC FROSTED	B22	2800	370	28=40	72	Ø44	10/100
CLAHAFR18WESFR	18W F/R HALOGEN ES FROSTED	E27	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WESFR	28W F/R HALOGEN ES FROSTED	E27	2800	370	28=40	72	Ø44	10/100
CLAHAFR18WSBCFR	18W F/R HALOGEN SBC FROSTED	B15	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WSBCFR	28W F/R HALOGEN SBC FROSTED	B15	2800	370	28=40	72	Ø44	10/100
CLAHAFR18WSESFR	18W F/R HALOGEN SES FROSTED	E14	2800	210	18=25	72	Ø44	10/100
CLAHAFR28WSESFR	28W F/R HALOGEN SES FROSTED	E14	2800	370	28=40	72	Ø44	10/100

Brochure updated on 13.12.2016