

Dies Hydraulic Tool Range

Dies for 23 Tonne Range

Copper			Aluminium	
Nominal Conductor (mm ²)	Catalogue No.	Copper Die A/F Hex (mm)	Aluminium Die Catalogue No.	A/F Hex (mm)
16 - 300	Use 12 Tonne Dies with adaptor		ECW-H3D-AD	
400	ECW-H3D-400	28.1	ECW-H3D4/500AL	39.0
500	ECW-H3D-500	31.0	ECW-H3D4/500AL	39.0
630	ECW-H3D-630	37.0	Not possible – use a RHU520	



Dies for 52 Tonne Range

Copper			Aluminium	
Nominal Conductor (mm ²)	Catalogue No.	Copper Die A/F Hex (mm)	Aluminium Die Catalogue No.	A/F Hex (mm)
16 - 300	Use 12 tonne dies with adaptor RHU520-AD			
400	RHU520-400	28.1	RHU520-4/500AL	39.0
500	RHU520-500	31.0	RHU520-4/500AL	39.0
600	RHU520-600			
630	RHU520-630	37.0	RHU520-800	43.2
800	RHU520-800	43.2	RHU520-800	43.2
1000	RHU520-1000	48.0	RHU520-1000AL	52.5



Dies for 60 Tonne Range

60 tonne "C" style crimping die sets to suit MSS-XH60 remote crimping head.

Copper Hex Dies			Aluminium Hex Dies			ACSR/AAC/AAAC	
Catalogue No.	AF mm	Conduit mm ²	Catalogue No.	AF mm	Conduit mm ²	Catalogue No.	AF mm
MSS-RH60-23.1AFCU	23.1	240	MSS-RH60-28.3AFAL	28.3	240/300	MSS-RH60-28.5AFAL	28.5mm
MSS-RH60-26.0AFCU	26.0	300	MSS-RH60-39.0AFAL	39.0	400/500	MSS-RH60-34.5AFAL	34.5mm
MSS-RH60-28.1AFCU	28.1	400	MSS-RH60-43.2AF	43.2	630/800	MSS-RH60-40.0AFAL	40.0mm
MSS-RH60-31.0AFCU	31.0	500	MSS-RH60-52.5AFAL	52.5	1000	MSS-RH60-44.5AFAL	44.5mm
MSS-RH60-37.0AFCU	37.0	630				MSS-RH60-47.5AFAL	47.5mm
MSS-RH60-43.2AF	43.2	800				MSS-RH60-48.0AFAL	48.0mm

