

Cable Stockings (Grips)

Tubular Single Eye

CABAC's "CG" range of stockings are the most common type of stockings, used for general cable hauling. They have a single eye and are integrally woven on a central axis. They are slipped over the end of the cable, and grip when pulled.

They are made of two ply, galvanised steel wire strand with an alloy ferrule and soft eye. Variations such as galvanised thimbles, copper ferrules, stainless steel strand and stainless steel thimbles are also available. Please contact our sales.

Catalogue No.	To Grip Cable Diameter (mm)	Grip Length Approx. (mm)	Max Pull Approx. (kN)
CG10	10-14	350	5
CG14	14-19	400	9
CG20	19-28	500	15
CG30	28-40	600	24
CG45	40-55	800	35
CG60	55-75	900	62
CG75	75-95	1000	98
CG105	95-120	1200	133
CG135	120-150	1400	187
CG165	150-190	1600	283



Ordering Variations

	Standard (No Suffix)	Variation	Suffix
Grip	Gal. Wire Rope	Stainless Steel Rope	SS
Ferrule	Alloy	Copper Ferrule Stainless Steel	CF SF
Eye	Soft	Galvanised Thimble Stainless Steel Thimble	GT ST

EG: Tubular single eye 60mm stocking in stainless steel with ferrule and eye - CG60-SS-SF-ST.

NB: If you wish to order a tubular single eye cable grip completely made of Stainless Steel for a 50mm dia cable you need to add suffixes to the catalogue number CG45 e.g. CG45 -SS-SF-ST. Please refer to the ordering variations table.

Tubular Offset Eye

CABAC's Offset Eye Style cable stockings allow the cable to be passed through the grip to allow it to be secured at any point along the cable. It is mainly used for strain relief, with typical applications being permanent installations in process plants, mines etc.

The standard offset eye style is manufactured from two ply galvanised strand with an alloy ferrule and soft eye. Variations such as galvanised thimbles, copper ferrules, stainless steel strand and stainless steel thimbles are also available. Please contact our sales.

Catalogue No.	To Grip Cable Diameter (mm)	Grip Length Approx. (mm)	Max Pull Approx. (kN)
CG100E	10-14	350	5
CG140E	14-19	400	9
CG200E	19-28	500	15
CG300E	28-40	600	24
CG450E	40-55	800	35
CG600E	55-75	900	62
CG750E	75-95	1000	98
CG1050E	95-120	1200	133
CG1350E	120-150	1400	187
CG1650E	150-190	1600	283



Ordering Variations

	Standard (No Suffix)	Variation	Suffix
Grip	Gal. Wire Rope	Stainless Steel Rope	SS
Ferrule	Alloy	Copper Ferrule Stainless Steel	CF SF
Eye	Soft	Galvanised Thimble Stainless Steel Thimble	GT ST

EG: Offset eye 20mm stocking in stainless with stainless ferrule and eye – CG200E-SS-SF-ST