

**CAT III  
500V**

# T2732 - Professional Analogue Insulation Tester 250, 500 & 1000V



## HOUSING

Compact rugged housing with soft rubber boot

## STRAPS FIXED TO STUDS

on rubber boot for easy to use position during use

## BATTERY INDICATION

## NEEDLE INDICATOR ADJUSTMENT

## SELECTOR SWITCH

High  $\Omega$  (250, 500 & 1000V)  
Low  $\Omega$  (0-3 $\Omega$  & 0-500 $\Omega$ )  
AC Voltage (0-600V)  
Colour coded

## BATTERY TEST

CATIII 500V

**ANALOGUE DISPLAY**  
Colour coded ranges

**WARNING LIGHT**  
For live line voltage

**PUSH DOWN BUTTON**  
(With lock)  
(Default V measurement) if button not activated

**ZERO ADJUSTMENT FOR LOW  $\Omega$**

**DEFAULT VOLTAGE MEASUREMENT**  
When test button not activated



## FEATURE

Insulation

## RANGE

0 to 100M $\Omega$  (250V DC  $\pm$  10%)

0 to 200M $\Omega$  (500V DC  $\pm$  10%)

0 to 400M $\Omega$  (1000V DC  $\pm$  10%)

## ACCURACY

$\pm$  5% of full scale

Continuity

0 to 3 $\Omega$

0 to 500 $\Omega$  210 mA

$\pm$ 1.0% of

full scale

AC Voltage

0 to 600V AC

$\pm$  3% of

full scale

Voltage

90VDC, 70VAC for Visual Indication

Warning

24V Buzzer

## ORDERING INFORMATION

Part No: **T2732**

The unit comes in a rubber holder with batteries, spare fuse, leads & crocodile clips, manual and shoulder strap.

Batteries: 6 x 1.5V AA

Fuse: 0.5A (5 x 20mm)

Size: L205 x W90 x T55mm

Weight: 540g with Batteries

For replacement test leads order AL24.

\*Refer to CABAC website [cabac.com.au](http://cabac.com.au) for terms and conditions on warranty.