

Tapes

Double Sided Tape

CABAC's Double Sided Tape has a high adhesive strength and is especially designed for holding, joining or bonding on a wide variety of surfaces. This alternative to fasteners offers the advantage of lower installation costs and is safe and easy to use.

- Material: Ethylene-Vinyl Acetate
- Adhesion: 0.25kg per sq cm
- Colour: White
- Thickness: approx 1mm

DST12 12mm x 10m

DST18 18mm x 10m

DST24 24mm x 10m



Construction Warning Tape

This tape is used to tape off and warn against hazardous or dangerous construction work zones. This durable, yet lightweight tape comes on an easy to use roll so that it can be put up quickly to block off large areas of construction wiring zones. The tape has the added advantage of being adhesive backed and waterproof.

- Material: PVC
- Gauge: 30 micron
- Colour: Flexoprint yellow with black lettering
- Reel Size: 36mm x 66m
- Made to AS:ANZ1635:1995

CCW38



Warning Marker Tape

Warning marker tape is laid in the ground close to the surface above the cable after partially back-filling the trench with soil or fill. It is a visual warning of the presence of electrical cables buried below.

- Electric orange colour, marked every metre in black with the words "Caution Electrical Cable Below".
- Material: Polyethylene 100mm nominal thickness
- Environmentally friendly – manufactured from recycled material
- Operating Temperature: -20°C to 120°C
- Accepting Authorities: Energy Australia, Integral Energy, Electricity Services Victoria, ERGON

WMT150 50m Roll x 150micron (width) x 0.7kg

WMT150/360 360m Roll x 150micron (width) x 4.8kg

WMT150/500 500m Roll x 150micron (width) x 7.0kg



Insulation Tape

Cabac's improved insulation tape has upgraded adhesive and elasticity properties. This high quality tape will provide easy application with long term adhesion. This tape can be used for basic insulation, and general wire wrapping.

The tape is supplied in packs of 10 in a rainbow pack, or in discrete single colour packs.

Technical Data

Nominal reel dimensions	20m long, 18mm wide
Tape backing	PVC
Adhesive	Rubber based
Thickness	0.13mm
Adhesion	1.8N/cm ²
Tensile strength	28.5N/cm ²
Elongation	<160%
Breakdown voltage	8kV
Dialectic Strength	42kV/mm

ITRP Rainbow pack

ITYL/10 Yellow pack of 10 rolls

ITWH/10 White pack of 10 rolls

ITBK/10 Black pack of 10 rolls

ITRD/10 Red pack of 10 rolls

ITBL/10 Blue pack of 10 rolls

ITYG/10 Yellow/Green pack of 10 rolls

