



A NEW FORCE IN CHEMICAL MANUFACTURING

Unit 2, 14-16 Lee Holm Road
St Marys NSW 2760
Australia

Ph: 1300 738 250 (Australia)
Ph: +61 2 9833 9766 (International)
Fax: 02 9623 3670

sales@chemtools.com.au
www.chemtools.com.au

TECHNICAL DATA SHEET

OCTOBER 2014

PRODUCT NAME

CT-GKS Gasket & Carbon Residue Stripper

PRODUCT RANGE

Part Number	Available Size
CT-GKS-500	500g Aerosol



Refer to MSDS for product safety guidelines

CT-GKS Gasket & Carbon Residue Stripper

Chemtools® Gasket & Carbon Residue Stripper has been developed to remove gasket residue from components quickly, easily, and with minimum effort. Once sprayed onto the gasket residue it will soften the gasket to allow easy removal without the need for excessive scraping that could be damaging to sensitive substrates, such as aluminium casings.

FEATURES AND BENEFITS:

- Easy to use
- Fast and effective
- Loosens synthetic, cork, and fibre gaskets
- Over spray will not damage engine parts
- Saves time and reduces scraping damage on alloys
- Easily removes baked-on gaskets
- Some applications will require no scraping
- Great for hard to reach areas

PHYSICAL PROPERTIES:

Appearance	Aerosol
Colour	Clear
Specific Gravity @25°C	0.9
Propellant	CO2
Shelf Life	3 Years (from date of manufacture)

DIRECTIONS FOR USE:

- Spray liberally onto the area to be stripped, holding aerosol approximately 30 cm away
- Allow 6 to 10 minutes for the product to penetrate
- Remove the old gasket with a scraper, or knife.
- If required, repeat again.

Once the old gasket is off, clean the surface using Chemtools® Prep-Solv, before assembling the new gasket.

STORAGE:

Store in a cool, dry place in tightly closed original containers, at a room temperature between 5°C to 40°C. Do not place in direct sunlight or near any heat source. Please do not return any used material to its original container.

PRECAUTIONS:

This product is capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the material.

WARRANTY:

All products purchased from or supplied by Chemtools® are subject to terms and conditions set out in the contract. Chemtools® warrants only that its products meet the specifications designated as such herein, or in other publications. All other information supplied by Chemtools® is considered accurate, but is furnished upon the express condition. The customer shall make its own assessment to determine the products suitability for a particular purpose. Chemtools® makes no other warranty, either expressed or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or products will not infringe any patent.