



CLEVERTRONICS LP PREMIUM CLEVERFIT LED THEATRE EXIT



PRODUCT INFORMATION

Catalogue Number	CCFLED-TH-R
Description	LED LP Premium Cleverfit Theatre Exit, 24 metre viewing Distance
Construction	ABS Body with ABS Diffuser and Polycarbonate Clear tamper proof cover.
Mounting	Wall, Ceiling Single-Sided & Ceiling Double-Sided
Dimensions L x W x H	355mm x 80mm x 215mm
Operating Mode	Maintained
Testing System	N/A - Manual Test Switch
Charging Method	Intelligent current limited constant voltage charger
Diffuser	Theatre Mask (must specify diffuser combination)
Lamp(s)	6 x high intensity, low energy LED, surface mounted onto a replaceable lamp bar, 100,000 hour
Operating Voltage	240V 50Hz
Power Consumption	2.7W Standby (5.1W during first 16hr charge)
IP Rating	IP20
Operating Temperature	1° to 40°C
AS/NZS2293 Classification	NA – Theatre Mask

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550190	Battery: LP 3.2 Volt 1.5Ah Li-ion
8002325	PCA: LP LED Cleverfit Driver, #CT10164-L4
8002120	PCA: DLED Cleverfit Light Strip, #CT10152-D2

