



## ELIFE-LI

### CLEVERTRONICS ECONOMY LIFELIGHT BASIC



#### PRODUCT INFORMATION

Part Number	ELIFE-LI
MIC	AUD03510030001
Description	Economy Lifelight Basic, Recessed Emergency Light
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 50mm x 42mm (Control Pack) 95mm Head Diameter (145mm with adaptor plate)
Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Depth	120mm, 70mm (with adaptor plate)
Weight	0.5kg
Operating Mode	Non-maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 1.3 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D32 C90=D32
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

#### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560100	BATT:Eco Lith 3.2V 1.5Ah 70mm lead, no BRKT
8050210	LED: HWSUB: HT10136-A3 - GW CSHPM 'LT'
AUM03570040001 ELIFE-LI-CKIT	DRIVER: Lifelight: LED, Eco, NM, Control Only, CT10460-L4

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.