



CLEVERTRONICS L10 ARGONAUT VANDAL BATTEN



PRODUCT INFORMATION

Catalogue Number	LVP4LEDM-P-DD-ZW
Description	L10 Optimum 4ft Argonaut LED Vandal Batten with Battery POD and LED Modules/Light Engines with Dali Driver
Construction	Pressure Die-cast, Low Copper Aluminium Alloy Body with Grey Powder Coat Paint Finish. Removable Gear Tray and Replaceable LED Modules. Battery POD at one end. (Retains Through-Conduit/Wiring Capability even with the POD)
Mounting	Surface Mount
Dimensions L x W x H	1400mm x 140mm x 120mm (including battery POD)
Operating Mode	Maintained
Testing System	Zoneworks Computerised Testing
Battery	Lithium Nanophosphate, 6.6V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Opal, Impact Resistant Polycarbonate with Secure Access Screws
Driver / Ballast	Tridonic LC 50W 350-1050mA ONE4ALL
Lamp(s)	2 x LED module, 4000K natural white, 50,000h [L80/ B20, Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	>0.9
Total lumen output	5300 lm @ 123lm/W
Power Consumption	44 Watts (Lamps ON), 0.4 Watts (Lamps OFF)
IP Rating	IP66
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D100 C ₉₀ =D40
Impact Rating	IK10

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530260	BATT:L10 6.6V 2500mA.SBS.
1330056	LED Driver - LC 50w 350-1050mA,ONEFORALL
8002699	PCA: LED Strip 5P8S, ALS-50-840-3-01-A
LCPLED-48V95C-CKIT	LED Power Pack, 48V 95mA, 6.6V 2.5Ah,L10
8001460	PCA:Pwrln Node ZW Horizontal #CT10310-A6

