



LLIFE-PRO-SMS-DALI-SPOT

Lifelight Pro Surface Mount Emergency Spotlight
L10 Nanophosphate, DALI



PRODUCT INFORMATION

Part Number	LLIFE-PRO-SMS-DALI-SPOT
MIC	AUT01210520102
Description	Lifelight Pro Surface Mount Emergency Spotlight, L10 Nanophosphate, DALI
Construction	PC/ABS Head, Metal Enclosure. Double/reinforced insulation between supply and battery circuit of lamp control gear.
Mounting	Surface Mounted
Dimensions L x W x H	267mm x 148mm x 60mm (base assembly) 105mm (lamp head and swivel assembly height)
Weight	2.0kg
Operating Mode	Non-Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3W (Max)
Inrush Current (Max)	0.347mA
Earth Leakage	13.313mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100869	LED Head Assembly
AUM01270260002 LLIFE-PRO-SMS-CKIT-DALI-NP	Driver Pack
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order