

CLEVERTRONICS LP LIFELIGHT SURFACE MOUNT (DALI)



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Catalogue Number | CLIFE-SM-DALI |
| MIC | AUD02210200002 |
| Description | LP Premium Lifelight, High Performance, Surface Mounted Emergency Light |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mount |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.6kg |
| Operating Mode | Non-maintained |
| Testing System | DALI Registered |
| Battery | Lithium Iron Phosphate, 3.2V 3200mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | 1 x High intensity LED |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 1.0 W (Standby), 3.9W (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D40 C ₉₀ =D40 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|---|
| 1550030 | BATT:LP 3.2V 3200mAh 260mm lead,noBRKT. |
| 8003060 | PCA: DALI Node #CT10629-Ax |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order