

CLEVERTRONICS LP LIFELIGHT SURFACE MOUNT (Zoneworks XT)



PRODUCT INFORMATION

Catalogue Number	CLIFE-SM-ZW
MIC	AUD02110010001
Description	LP Premium Lifelight, High Performance, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 W (Standby), 3.9W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	BATT:LP 3.2V 3200mAh 260mm lead,noBRKT.
8001450	PCA:Powerline Node ZW, #CT10310-A6

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order