

42E350RUD2M-VW

Clipsal Iconic - 350 W Universal Rotary Dimmer -
230V - Vivid White



Main

Range	Clipsal Iconic
Product or component type	Dimmer
Device presentation	Mechanism
Dimmer type	Universal

Complementary

Range compatibility	Clipsal Iconic
Fixing mode	Clip-in
Colour tint	Vivid white (VW)
Surface finish	Glossy
Type of packing	Box
Ambient air temperature for storage	0...60 °C
Dimmer control	315° rotary setting
[Ie] rated operational current	1.5 A
[Ue] rated operational voltage	220...240 V AC 50 Hz 1 W
Load type	Dimmable LED 350 W (240 V AC) Incandescent 350 W (240 V AC) Low voltage halogen lamp with electronic transformer 350 W (240 V AC) Dimmable fluocompact lamp 150 W (240 V AC) Low voltage halogen lamp with iron core transformer 350 W (240 V AC) Dimmable fluorescent 150 W (240 V AC)
Derating factor	Number of devices 1 350 W without derating Number of devices 2 250 W with derating Number of devices 3 150 W with derating
Function available	Brightness adjustment
Protection type	Short-circuit
Control type	Rotary knob
Connections - terminals	Flying leads
Material	PC (UL94 V-2) for top PC MAS056 (UL94 V-2) for bottom
Height	22.5 mm
Width	22.5 mm
Depth	39 mm
Embedding depth	37 mm
Standards	AS/NZS 60669.2.1

Environment

ambient air temperature for operation	0...45 °C
relative humidity	0...90 %

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1713 - Schneider Electric declaration of conformity
REACH	Reference contains SVHC above the threshold

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.