



Main

Range	Clipsal
Product name	TPWL Series
Product or component type	Wall light
Device application	Lighting

Complementary

Type of installation	Outdoor Indoor
Operational power in W	6 W
Light source	LED
[Ue] rated operational voltage	240 V AC 50 Hz
Colour rendering index	R <sub>a</sub> =70
Luminous flux	660 lm
Bulb lifespan	36000 h
Colour temperature	4000 K
Colour	Silver grey body
Device mounting	Wall mounted
Mounting mode	Wall-mounted
Quantity per set	2
Fixing mode	By mounting plate brackets
Height	239 mm
Width	70 mm
Depth	106 mm
Targeted country	Australia

Environment

IP degree of protection	IP54
ambient air temperature for operation	-10...40 °C
relative humidity	10...95 % non-condensing

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.