

## Product data sheet

### Characteristics

# 3041VA-XW

Switch, Iconic, 1 gang, vertical, 1 or 2 way, 20 A / 16 AX, White



### Main

|                           |           |
|---------------------------|-----------|
| Range                     | Iconic    |
| Product or component type | Switch    |
| Device application        | Lighting  |
| Colour tint               | White     |
| Type of packing           | Polybag   |
| Quantity per set          | Set of 10 |

### Complementary

|                                |                                                                                                                                                                  |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device presentation            | Complete product                                                                                                                                                 |
| Control type                   | Rocker                                                                                                                                                           |
| Device mounting                | Wall                                                                                                                                                             |
| Installation direction         | Vertical                                                                                                                                                         |
| Switch function                | 1-pole 1/2-way                                                                                                                                                   |
| Number of rocker               | 1                                                                                                                                                                |
| Rated current                  | 20 A/16 AX                                                                                                                                                       |
| [Ue] rated operational voltage | 250 V                                                                                                                                                            |
| Material                       | PC (polycarbonate)<br>PP (polypropylene)<br>ABS (acrylonitrile butadiene-styrene)<br>POM (polyoxymethylene)                                                      |
| Fixing mode                    | By screws                                                                                                                                                        |
| Surface finish                 | Glossy                                                                                                                                                           |
| Surface treatment              | Untreated                                                                                                                                                        |
| Connections - terminals        | Screw terminal                                                                                                                                                   |
| Clamping connection capacity   | 1 x 1.5...4 x 1.5 mm <sup>2</sup> for rigid or stranded cable(s)<br>3 x 2.5 mm <sup>2</sup> for stranded cable(s)<br>1 x 4 mm <sup>2</sup> for stranded cable(s) |
| Height                         | 116 mm                                                                                                                                                           |
| Width                          | 78 mm                                                                                                                                                            |
| Depth                          | 38 mm                                                                                                                                                            |
| Net weight                     | 0.067 kg                                                                                                                                                         |

### Environment

|                                       |           |
|---------------------------------------|-----------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity                     | 10...95 % |
| Product certifications                | RCM       |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 0.075 kg |
| Package 1 Height             | 39 mm    |
| Package 1 width              | 83 mm    |
| Package 1 Length             | 125 mm   |

## Offer Sustainability

|                            |                                                                                                                                 |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                           |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                             |
| RoHS exemption information |  <a href="#">Yes</a>                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a> |