



## Dektite® Premium

More Flexible sizing  
for better coverage



- ☒ Low profile base with watershed sleeve  
Improves water run off and protects silicone sealant
- ☒ Larger square base will cover a larger opening  
So more forgiving for penetration openings and allows for steeper roof pitch
- ☒ Unique cone design  
Provides 10mm (½") continuous contact with flashed pipe providing a watertight seal
- ☒ Clear markings in metric and imperial measurements  
Makes for easier cutting to pipe size
- ☒ Size Ranges - Numbers 0-9  
Available in Black and Grey EPDM, and Red Silicone
- ☒ Twenty year warranty  
Just fit it and forget it - we've got you covered

# Selection Guide

DEKS Code			Description	Pipe OD		Base		Pitch	Carton QTY
Black EPDM	Grey EPDM	Red Silicone		mm	inch	mm	inch		
DFE10MB	DFE10MG	DFE20MRE	Dektite Premium Micro	0 - 20	0 - 3/4"	71 x 71	2 3/4 x 2 3/4"	0-45° or 12/12	20
DFE100B	DFE100G	DFE200RE	Dektite Premium #0	0 - 35	0 - 1 1/2"	100 x 100	4 x 4"	0-45° or 12/12	20
DFE100BS	DFE100GS	DFE200RES	Dektite Premium #0 Solar	0 - 35	0 - 1 1/2"	100 x 100	4 x 4"	0-45° or 12/12	20
DFE101B	DFE101G	DFE201RE	Dektite Premium #1	0 - 55	1/4 - 2 1/4"	139 x 139	5 1/2 x 5 1/2"	0-45° or 12/12	15
DFE101BS	DFE101GS	DFE201RES	Dektite Premium #1 Solar	5 - 55	1/4 - 2 1/4"	139 x 139	5 1/2 x 5 1/2"	0-45° or 12/12	15
DFE102B	DFE102G	DFE202RE	Dektite Premium #2	5 - 76	1/4 - 3"	178 x 178	7 x 7"	0-45° or 12/12	15
DFE102BA	DFE102GA	DFE202REA	Dektite Premium 50-70	50 - 70	2 - 2 1/4"	178 x 178	7 x 7"	0-45° or 12/12	15
DFE103B	DFE103G	DFE203RE	Dektite Premium #3	5 - 127	1/4 - 5"	221 x 221	8 3/4 x 8 3/4"	0-45° or 12/12	15
DFE104B	DFE104G	DFE204RE	Dektite Premium #4	75 - 175	3 - 7"	280 x 280	11 x 11"	0-45° or 12/12	10
DFE105B	DFE105G	DFE205RE	Dektite Premium #5	100 - 200	4 - 8"	310 x 310	12 1/2 x 12 1/2"	0-45° or 12/12	10
DFE106B	DFE106G	DFE206RE	Dektite Premium #6	125 - 230	5 - 9"	363 x 363	14 1/4 x 14 1/4"	0-45° or 12/12	10
DFE107B	DFE107G	DFE207RE	Dektite Premium #7	150 - 300	6 - 12"	456 x 456	18 x 18"	0-45° or 12/12	10
DFE108B	DFE108G	DFE208RE	Dektite Premium #8	170 - 355	6 3/4 - 14"	496 x 496	19 1/2 x 19 1/2"	0-45° or 12/12	5
DFE109B	DFE109G	DFE209RE	Dektite Premium #9	230 - 508	9 - 20"	681 x 681	26 3/4 x 26 3/4"	0-45° or 12/12	5

## Available in Black and Grey EPDM or Red Silicone

EPDM will withstand constant temperatures at the roofline of -50°C (-58°F) to 115°C (239°F) and up to 150°C (302°F) intermittently  
Red Silicone will withstand constant temperatures at the roofline of -50°C (-58°F) to 200°C (392°F) and up to 250°C (482°F) intermittently

**Please Note** That the outside temperature of the pipe may be significantly different to the exit temperature of the appliance.

## Installation Information



**1**  
Trim the cone to suit pipe size using sharp tin snips.



**2**  
Slide down pipe using water as a lubricant.



**3**  
Apply sealant by turning back flexible flange.



**4**  
Press base to the roof profile by hand. Smooth out any awkward creases. Don't fully extend to allow for vibration.



**5**  
Fasten using self-sealing fasteners or pop (sealed) rivets.



**\***  
A Dektite may be fitted on the 'diamond' for enlarged holes and penetrations on steep pitched roofs up to 45° or deep corrugations

- Always use the neutral cure low modulus silicone for sealing
- In corrosive and coastal environments fix using blind aluminium rivets

**Need to flash a tiled roof? Contact DEKS to discuss the tile roof flashing range.**