









	Voltage U_s V	For use with	Contact sequence	Part no. Article no.	Price see price list	Std. pack	Notes					
Suppressors												
RC suppressors												
	24 – 48 AC	DILMP20		DILM12-XSPR48 281199		10 off	For AC-operated contactors 50 – 60 Hz. With DC operated contactors and with DILM115 and DILM150 or DILMP125 to DILMP 200 the suppressor is integrated. Note drop-out delay					
	110 – 240 AC			DILM12-XSPR240 281200								
	240 – 500 AC			DILM12-XSPR500 281201								
	24 – 48 AC	DILMP32 DILMP45		DILM32-XSPR48 281202								
	110 – 240 AC			DILM32-XSPR240 281203								
	240 – 500 AC			DILM32-XSPR500 281204								
	24 – 48 AC	DILMP63 DILMP80		DILM95-XSPR48 281205								
	110 – 240 AC			DILM95-XSPR240 281206								
	240 – 500 AC			DILM95-XSPR500 281207								
Varistor suppressors												
	24 – 48 AC	DILMP20		DILM12-XSPV48 281208		10 off	For AC-operated contactors 50 – 60 Hz. With DC operated contactors and with DILM115 and DILM150 or DILMP125 to DILMP 200 the suppressor is integrated. Note drop-out delay					
	48 – 130 AC			DILM12-XSPV130 281209								
	130 – 240 AC			DILM12-XSPV240 281210								
	240 – 500 AC	DILM12-XSPV500 281211										
	24 – 48 AC	DILMP32 DILMP45		DILM32-XSPV48 281212								
	48 – 130 AC			DILM32-XSPV130 281213								
	130 – 240 AC			DILM32-XSPV240 281214								
	240 – 500 AC	DILM32-XSPV500 281215										
	24 – 48 AC	DILMP63 DILMP80		DILM95-XSPV48 281216								
	48 – 130 AC			DILM95-XSPV130 281217								
	130 – 240 AC			DILM95-XSPV240 281218								
	240 – 500 AC	DILM95-XSPV500 281219										
	Varistor suppressors with integrated LED											
		24 – 48 AC		DILMP20					DILM12-XSPVL48 281220		10 off	For AC-operated contactors 50 – 60 Hz. With DC operated contactors and with DILM115 and DILM150 or DILMP125 to DILMP 200 the suppressor is integrated. Note drop-out delay
		130 – 240 AC							DILM12-XSPVL240 281221			
24 – 48 AC		DILMP32 DILMP45	DILM32-XSPVL48 281222									
130 – 240 AC			DILM32-XSPVL240 281223									
24 – 48 AC		DILMP63 DILMP80	DILM95-XSPVL48 281224									
130 – 240 AC			DILM95-XSPVL240 281225									
Free-wheel diode suppressor												
		12 – 250 DC	DILMP20		DILM12-XSPD 101672		10 off		In addition to the built-in suppressor circuit for DC actuated contactors. Prevents negative breaking voltage when contactors are used in combination with a safety PLC.			