


Head Office:

1/13 Cooper St. Smithfield NSW 2164
P.O. Box 2084, Smithfield NSW 2164
Tel: (02) 8786 5200
Fax: (02) 8786 5288

Victoria Branch:

460-464 Hammond Rd.
Dandenong South, VIC 3175
Tel: (03) 9706 6819
Fax: (03) 9768 3580

Queensland Branch:

118 Sandstone Place
Parkinson, QLD 4115
Tel: (07) 3271 6600
Fax: (07) 3809 0411

Western Australia Branch:

24 Harrison Rd.
Forrestfield, WA 6058
Tel: (08) 9454 2628
Fax: (08) 9454 3026

Conductor:

Class 6 of plain annealed copper conductor to AS/NZS 1125

(Except 2.5&4mm² that is Class 5)

Can also be operated at temperatures up to 90°C

when not exposed to mechanical deformation (see AS/NZS 3008.1)

Insulation: V-90 PVC

Colours:

2C+E--red, black, green/yellow;

3C+E--red, white, blue, green/yellow;

4C+E--red, white, blue, black, green/yellow.

Sheath: 5V-90 PVC

Colours: Orange

NO.	Code	Core No.	×	Cross-section mm ²	+	Earth core section mm ²	Core insulation thickness mm	Earth insulation thickness mm	Sheath thickness mm	O/D mm
1	FSRC2040E	2	×	4	+	2.5	1.0	0.8	1.8	13.0
2	FSRC2060E	2	×	6	+	2.5	1.0	0.8	1.8	14.0
3	FSRC2100E	2	×	10	+	4	1.0	1.0	1.8	16.0
4	FSRC2160E	2	×	16	+	6	1.0	1.0	1.8	18.0
5	FSRC2250E	2	×	25	+	6	1.2	1.0	1.8	22.0
6	FSRC2350E	2	×	35	+	10	1.2	1.0	1.8	24.0
7	FSRC2500E	2	×	50	+	16	1.4	1.0	1.9	29.0
8	FSRC3040E	3	×	4	+	2.5	1.0	0.8	1.8	15.0
9	FSRC3060E	3	×	6	+	2.5	1.0	0.8	1.8	16.0
10	FSRC3100E	3	×	10	+	4	1.0	1.0	1.8	18.0
11	FSRC3160E	3	×	16	+	6	1.0	1.0	1.8	20.0
12	FSRC3250E	3	×	25	+	6	1.2	1.0	1.8	24.0
13	FSRC3350E	3	×	35	+	10	1.2	1.0	1.8	26.0
14	FSRC3500E	3	×	50	+	16	1.4	1.0	1.9	31.0
15	FSRC4040E	4	×	4	+	2.5	1.0	0.8	1.8	16.0
16	FSRC4060E	4	×	6	+	2.5	1.0	0.8	1.8	17.0
17	FSRC4100E	4	×	10	+	4	1.0	1.0	1.8	20.0
18	FSRC4160E	4	×	16	+	6	1.0	1.0	1.8	22.0
19	FSRC4250E	4	×	25	+	6	1.2	1.0	1.8	26.0
20	FSRC4350E	4	×	35	+	10	1.2	1.0	1.9	29.0
21	FSRC4500E	4	×	50	+	16	1.4	1.0	2.1	35.0



Quality ISO 9001
Certified System

Note: Other types or other lengths of the above cables can be manufactured according to customers' specifications.