



FEATURES

- Five-colour switchable
- Dual power switchable
- Large 6mm terminal block for easy installation
- High impact body and diffuser
- Stainless steel clips and screws
- IP65 weatherproof and IK08 vandal-proof
- Side and rear cable entry options

INCLUDES

- IP65 batten with LED driver
- Stainless steel clips and screws
- Suspension brackets and cable gland

INSTALLATION OPTIONS

- Surface mounted
- Suspended (Suspension kit is required)

APPLICATIONS

- Warehouses
- Car parks and garages
- Stations
- Food preparation areas
- Commercial

WARRANTY

- Five years for fitting

CERTIFICATION	IP RATING	FIVE-COLOUR	L70B50	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
							 1.7kg at 300mm

Order Code	Part No.	Model No.	Voltage	Watt.	PF	Color Temp.	Lumens ^[3]	Beam Angle	Size(L*W*H) mm	Net Weight (kg)
211021	211021	WPB1-FC-N-2L60 20W	220-240V	10/20W	0.9	3000/4000/5000/5700/6500K	1000/2000lm	120°	655*115*86	1.28
211022	211022	WPB1-FC-N-2L120 40W	220-240V	20/40W	0.9	3000/4000/5000/5700/6500K	2000/4000lm	120°	1265*115*86	2.15

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+45 °C

[3] 3000K Lumen: 10/20W 930/1860lm
20/40W 1860/3720lm

[4] Flicker Free option available, made to order

