



Representative Photo Only
(actual product may vary based on configuration selections)

Modular Step Relay 16A 1 N/O 1 N/C 24V AC Coil

- Complete range from PCB to power relays to cover all of your switching requirements
- International certifications and approvals including CE, CSA, EAC, PCT, RINA, VDE and RoHS, providing quality assurance of a market leading product
- Compact construction allowing for most efficient use of your space

SPECIFICATIONS

Component Type	Timers and Control relays	Relay
Contact Configuration	1 NO + 1 NC	
In, Rated Current	16 A	
Icw, Short Time Withstand Current, 10ms (rms)	30 A, 10ms	
Un, Nominal Operational Voltage, AC	250 V AC	
Ue, Rated Operational Voltage, AC, max	400 V AC	
Rated Load, AC-1	4000 VA	
Rated Load, AC-15	750 VA	
Coil Type	AC	
Coil Voltage, AC, Nom	24 V AC	
Coil Voltage, AC, Min	20.4 V AC	
Coil Voltage, AC, Max	26.4 V AC	
Material, Contacts	Silver Nickel (AgNi) material	
Mechanical service life	300000 cycles	
Electrical Service Life at Un, In	100000 cycles	
IP Rating	IP20	
Insulation Voltage, between Coil & Contacts	4000 V	
Dielectric Strength, between open Contacts	2000 V AC	
Mounting	DIN-35 Rail Mount	
Operating Temperature, min	-40 °C min	
Operating Temperature, Max	40 °C max	
Vibration Duration (Max.)	60 min	
Certifications	CE EAC IMQ GOST-R C-UR-US	



