

properties

- Highly flexible
- Accepts torsional movement
- Vibration and shock tested to EN61373 Cat 2
- IP rating: IP65
- Temperature range
 - 5°C to +70°C (FPCB - black)
 - 20°C to +70°C (FPCG - grey)
 - 20°C to +70°C (FPCGN - green)
 - 20°C to +90°C (FPCBU - blue)
- FPCB (black) is UV resistant
- FPCGN (green) is oil resistant
- Self extinguishing
- Metric threads supplied complete with locknuts
- UL recognised to UL1696 for use in US and Canada



IP65

MPC90

90° elbow nylon
compression fitting
external thread

2 part compression, 90 degree elbow fitting with internal spigot and all round external teeth to grip conduit. Available in black or grey (RAL 7001).

IP65

MPC45

45° elbow nylon
compression fitting
external thread

2 part compression, 45 degree elbow fitting with internal spigot and all round external teeth to grip conduit. Available in black or grey (RAL 7001).



metric thread
part number

PG thread
part number



metric thread
part number

MPC90-16-M16	MPC90-16-PG11	MPC45-16-M20
MPC90-16-M20	MPC90-16-PG13	
MPC90-20-M20	MPC90-20-PG16	MPC45-20-M20
MPC90-25-M25	MPC90-25-PG21	MPC45-25-M25
		MPC45-32-M32
MPC90-32-M32	MPC90-32-PG29	
MPC90-40-M40	MPC90-40-PG36	

STANDARDS



BS EN IEC 61386



* refer to conduit properties for applicable standards

TECHNICAL DRAWING

