

FPC Conduit - IP65

Cut Lengths - purchased in increments of 5 Metres

Typical application for type FPC conduit and fittings includes routing of cables within machines.

Construction: Smooth bore, helically formed PVC, flexible conduit with spiral UPVC reinforcement and flexible PVC jacket.

Colour: Black

Typical Applications: Routing of cables within machines

- High flexible
- Accepts torsional movement
- High impact resistance
- IP rating IP66
- Temperature range – 5°C to 70°C
- Self extinguishing



Hamer Code	Part No.	Reel Length (m)	Nominal Size (mm)	Outside Dia. (mm)	Inside Dia. (mm)	Min Inside Bend Radius (mm)
FL8012	FPC12B	30	12	14.5	10	25
FL8016	FPC16B	30	16	16.5	12.0	25
FL8020	FPC20B	30	20	21.0	16.0	35
FL8025	FPC25B	30	25	24.7	20.0	45
FL8032	FPC32B	30	32	33.5	28.0	60

MPC Fittings - IP65- Suitable for FPC Conduit

Type MPC External thread including locknut. Straight nylon PA66 compression fitting with external thread including locknut.

Hamer Code	Part No.	Thread
FL8512	MPC-12-M61B	M16
FL8516	MPC-16-M16B	M16
FL8518	MPC-16-M20B	M20
FL8520	MPC-20-M20B	M20
FL8525	MPC-25-M25B	M25
FL8532	MPC-32-M32B	M32



Type MPC90 90° elbow nylon - IP65 2 part compression, 90° elbow fitting with internal spigot and all round external teeth to grip conduit.

Hamer Code	Part No.	Thread
FL8716	MPC90-16-M61B	M16
FL8720	MPC90-20-M20B	M20
FL8725	MPC90-25-M25B	M25
FL8732	MPC-32-M32B	M32

