



garland
cables

pro series


Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


Part No: MC76S

Description	Stranded 24AWG (7/0.2mm) TACW, 6Cores, PVC Insulation, Aluminium Polyester Tape Overall Screen, 24AWG (7/0.2mm) TACW Drain Wire, PVC Sheath.
Applicable Standards	AS/CA S-008, UL758, EIA-RS232, AS 1049
Suitable Applications	For use in the communications, industrial and security sectors, This product can be used to interconnect DTE equipment such as Printers, fax's, modems, and consoles. In the industrial environment, this product can be used to connect instruments and sensors to data loggers, PLC's and other control equipment. In the security market, this product can be used to connect motion sensors, entry sensors, card readers and door strikes to monitoring units. Not suitable for direct connection to mains equipment.

Cable Construction Drawing



Cable Construction Relative Parts



Cable Description

Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
	24	7/0.2mm	0.22	0.6	TACW
Insulation	Cores : 6 Material : PVC Colour : White, Blue, Red, Black, Yellow, Green Nominal Thickness (mm) : 0.28 Nominal OD (mm) : 1.2				

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland

made by





garland
cables

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Drain Wire	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
	24	7/0.2	0.22	0.6	TACW
Screen	Material : Al. Polyester Tape				Coverage : 100%
Sheath	Material : PVC Colour : Grey(RAL 7046) Nominal Thickness (mm) : 0.7 Nominal OD (mm) : 5.5				

Electrical Properties

Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	95.3Ω/km
Min. Insulation Resistance @ 20°C	50MΩ.km
Voltage Test: Conductor to core	1.5 kV ac/1min
Voltage Test: Core to sheath	3.0 kV ac/1min

Mechanical Properties

Operating Temperature Range	-15 to 70°C
Max. Recommended Pulling Tension	92N
Min. Bend Radius (install)	55mm
Approximate Mass	4.3kg/100m

Sheath Printing  GARLAND DATA CABLE MC76S - AWM 2464 80°C
300V 6 X 7/0.2 24AWG OAS - MM/YYYY - "Mmark"

Supply Information

Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
100m	Plastic Reel	10 x 4.5 x 3.5"	4R	
300m	Reel Box	15.5 x 15.5 x 7.75"	1Box	
500m	Wooden Reel	W36 x 21.8cm	1R	36

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland





garland
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Document Change Record	Issue	Date	Prepared by	Approved By
	01	29-11-2012	YDM	Pent
Change History	Issue	Change		

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland

made by



madison