



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.


Part No: MCT7038S

Description	Stranded 20 AWG PACW, 8 Triad, V-90 PVC Insulated, Al. Polyester Tape Overall Screen, TACW 22AWG Drain Wire, 5V-90 PVC Sheath.	
Applicable Standards	AS/NZS 1125, AS/NZS 3808	
Suitable Applications	Instrument and control cable for use in industrial applications including the interconnection of signals between cabinets, consoles, sensors and display panels. Can also be used for carrying low bit rate data signals. Not intended for direct connection to mains power.	

Cable Construction Drawing

Cable Construction Relative Parts







Cable Description						
Conductor	AWG	Area(mm ²)	Stranding	Diameter(mm)	Material	
	20	0.5	7/0.3	0.9	PACW	
Insulation	Triad :		8	8		
	Material :		V-90 PVC	V-90 PVC		
	Colour:			Black, white & red wires form a triad. An ident. number is printed on each triad.		
	Nominal Thickness (mm) :		: 0.35	0.35		
	Nominal OD (mm):		1.65	1.65		

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Drain Wire	AWG	Area(mm ²)	Standing	Diameter(mm)	Material	
	22	0.343	7/0.25	0.75	TACW	
Overall Screen	Material : Al. Polyester Tape		ре	Coverage: 100%		
Sheath	Material :		5V-90 PVC			
	Colour:		Black	Black		
	Nominal Thickness (mm):		: 0.9	0.9		
	Nominal OD (mm):		13.0			

Electrical Properties	
Max. Conductor DC Resistance @ 20°C	$38.4\Omega/\text{km}$
Suggest Voltage Rating	110a.c/150d.c

Mechanical Properties	
Operating Temperature Range	-15 to 90°C
Max. Recommended Pulling Tension	840N
Min. Bend Radius (install)	130mm
Approximate Mass	24.1kg/100m

Supply Information						
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet		
500m	Wooden Reel	W65 x H51cm	1R			

- Madison reserves the right to make changes to the products described in this specification without
- All values subject to factory tolerances

