



garland
cables

pro series

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Figure 8 Cable


Part No: TCW14GY

Description	Stranded 21AWG (14/0.2mm) PACW, Figure 8 construction, PVC Insulation.
Applicable Standards	AS/CA S-008
Suitable Applications	For the wiring of electronic and allied equipment, extension speakers, security system etc.

Cable Construction Drawing



Cable Construction Relative Parts



Cable Description

Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
	24	14/0.2	0.215	0.6	PACW
Insulation	Cores : 2 Material : PVC(Agate Grey RAL 7046) Colour : Grey/Black Strip Nominal Thickness (mm) : 0.6 Nominal OD (mm) : 2.2 x 4.4				

Electrical Properties

Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	45.2 Ω /km
Min. Insulation Resistance @ 20°C	50M Ω .km

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland

made by





Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Voltage Test: Conductor to core	1.5 kV ac/1min
---------------------------------	----------------

Mechanical Properties

Operating Temperature Range	-15 to 70°C
-----------------------------	-------------

Max. Recommended Pulling Tension	61N
----------------------------------	-----

Min. Bend Radius (install)	22mm
----------------------------	------

Approximate Mass	1.75kg/100m
------------------	-------------

Sheath Printing

 GARLAND FIGURE 8 TCW14 - 2 X 14/0.2

Supply Information

Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
100m	Plastic Reel	7 x 4.5 x 3.5"	20R	

Document Change Record	Issue	Date	Prepared by	Approved By
	01	05-12-2012	LLS	Pent
Change History	Issue	Change		

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland

