

Data Sheet

USB Charger Power Boards

CAT NO. D104PAUSBWE, D105PAUSBWE



D104PAUSBWE



D105PAUSBWE

Cat No	D104PAUSBWE	D105PAUSBWE
Description	4-way switched powerboard with USB	4-way powerboard with USB
Colour	White	
Nominal input voltage	230-240V a.c 50 Hz	
Total Loading	10A 2400W	
Clamping voltage	775V	
Surge Protection	525 Joules	175 Joules
Stand-by power consumption at V_{in}	$\leq 0.15W$	
USB charging capacity	2 x 2.1A	2 x 1.0A
Overload protection (USB circuit)	4.6A \pm 0.1A	2.5A \pm 0.1A
Powerboard overload protection	10A	
Cord Length	1.8m	1.5m

USB Charger Power Boards

CAT NO. **D104PAUSBWE, D105PAUSBWE**



		D104PAUSBWE	D105PAUSBWE
Single Product	Quantity	1	1
	Dimensions	135mmW x 350mmH x 50mmD	103mmW x 550mmH x 50mmD
	Weight	.65kg	.44kg
	Barcode	9321001432425	9321001432395
Inner Box	Quantity	4	6
	Dimensions	210mmW x 370mmH x 145mmD	310mmW x 560mmH x 113mmD
	Weight	2.8kg	2.8kg
Outer Box	Quantity	24	36
	Dimensions	375mmW x 635mmH x 295mmD	620mmW x 560mmH x 320mmD
	Weight	18.9kg	18kg
	Barcode	9321001432449	9321001432418

- 4-way powerboards with USB
- 2 USB ports:
 - 4.2A max for D104PAUSBWE (charge up to 2 tablets simultaneously or 1 tablet and 1 smartphone)
 - 2.1A max for D105PAUSBWE (charge up to 2 smartphones simultaneously or 1 tablet only)
- Overload protection
- Surge protection with indicator
- Long lead (1.8m for D104PAUSBWE and 1.5m for D105PAUSBWE)
- 3 year warranty

HPM Legrand - AUS
1300 369 777
www.hpm.com.au
ABN 31 000 102 661

HPM Legrand - NZ
0800 476 009
www.hpm.co.nz

Refer to your group buying office, HPM Legrand Sales Representative or HPM Legrand Sales Office for pricing.