



VF312PT

Sm.distr, golf, flush, 36M, white door DZA

Architecture

| | |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

Functions

| | |
|---------------------|-----|
| With a pipe-in lead | yes |
|---------------------|-----|

Compatibility

| | |
|-----------------------------------|-----|
| Compatible with DIN rail mounting | yes |
|-----------------------------------|-----|

Main electrical features

| | |
|-----------------|-------|
| Nominal voltage | 400 V |
|-----------------|-------|

Cover, door

| | |
|------------------------------------|----------------|
| Cover type | Closed (plain) |
| Transparent cover or door | no |
| Cover type | Door |
| Door locking | without |
| Type of door closing | Latch |
| Door leave | single |
| Door quantity | 1 |
| Identification od protection index | 40 |
| Interlockable | no |

Materials

| | |
|---------------------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
| Colour | white |
| Colour | pure white |
| Material | plastic |
| Type of surface treatment | untreated |

Dimensions

| | |
|-----------------------------|---------|
| Insertion depth | 72 mm |
| Depth of installed product | 97,5 mm |
| Internal depth | 97,5 mm |
| Height of installed product | 543 mm |
| Built-in height | 507 mm |
| Built-in width | 318 mm |

Technical Properties

| | |
|----------------------------|--------|
| Width of installed product | 352 mm |
| Width in division units | 12 |

Installation, mounting

| | |
|--------------------------|----|
| Suitable for outdoor use | no |
|--------------------------|----|

Accessories included

| | |
|-------------------------|----|
| Mounting plate included | no |
| With lock | no |

Equipment

| | |
|------------------------------|-----|
| Number of rows | 3 |
| Quantity of section in width | 1 |
| Can be accessorized | yes |
| Quantity of rails | 3 |

Safety

| | |
|---|---------------|
| Protection class | isol.class II |
| Protection index IP | IP40 |
| IK protection code against mechanical impacts | IK07 |
| Halogen free | yes |
| Ultraviolet resistant | no |

Use conditions

| | |
|-----------------------|-----------|
| Operating temperature | -25 40 °C |
|-----------------------|-----------|