Recess Aluminium White

Recessed Wall Light

Name	Reces & Mini Reces				
Material	Aluminium				
Colour	Poly Powder Coated White				
IP Rating	IP67				
Colour Temp	3000k 4000k 5500k				
IK Rating	IK10				
Installation Type	Wall - Recessed				
Diffuser Type	Frosted Glass				
Lamp Base	Built in LED				
Max Wattage	2.5w or 1w				
Protection Class	s 3 (Low Voltage - No Earth Required)				
Lamp Expectancy	<30,000hrs*				
CRI	CRI>80				
SDCM	<6				
UGR	<17				
Dimmable	Yes - Triac Dimmable				
Warranty	3 Years Replacement*				



HV3205T-WHT-12V



HV3206T-WHT-12V











Terms & Conditions







Product Ordering

Image	Part Number	Colour Temp	Lumens	Input Voltage	Beam Angle	Included LED	Barcode
	HV3205T-WHT-12V	3000K 4000K 5500K	180lm 185lm 190lm	- 12v DC	40°	TRI Colour 2.5w Built in LED	9350418027979
	HV3206T-WHT-12V		55lm 57lm 60lm			TRI Colour 1w Built in LED	9350418028006

HV3205T-WHT-12V Dimensions HV3206T-WHT-12V Dimensions **Cutout with Canister Cutout without Canister** Ø76 Cutout without Caniste CANISTER Ø50 CANISTER Ø76 Ø50

Optional Havit Compatible Accessories

Image	Part Number	Description				
Triac Dimmer + Drivers						
Act I	HV9625	Triac Dimmer to suit Triac Dimmable Drivers				
Intelligency on any one of the second	12v DC Non Dimmable LED Drivers	See Catalogue or Website for full range of Non Dimmable 12v DC LED Drivers				
	12v DC Triac Dimmable LED Drivers	See Catalogue or Website for full range of 12v DC Triac Dimmable LED Drivers				

Dali Relay Modules


, · · · · · · · · · · · · · · · ·							
- Sale	HV9107-2303SAC-HP	Dali Dimmable Relay Module to be used with Triac Dimmable LED Drivers when Dali Control is required					
Media and a second	HV9107-2701S-N	Dali On-Off Relay Module to be used with Non Dimmable LED Drivers when Dali Control is required					

Related Products

HV3215T-WHT-12V HV3216T-WHT-12V







Other Available Colours

Antique



Solid

