



Product Code: LC4P1X4-65

IDE LC4P1X4-65 Transparent Lid With E+N Bars 4-Module 1-Row Halogen-Free Plastic RAL 7035 Grey Surface Mount IP65

- Robust polycarbonate enclosure, IP65 rated
- Surface mount with 125A current capacity
- Halogen-free plastic, RAL 7035 light grey
- Transparent window with tinted PC lid
- Top, bottom, and oblong rear cable entry

Specifications

Product Type	Load Centre
Brand	IDE
Ambient Temperature	-25 to 40 deg C
Ball Pressure Test	70 deg C
Cable Entry	Top, Bottom, Oblong Rear
Colour	RAL 7035 Light Grey
Degree of Protection	IP65
Depth	113 mm
Height	231 mm
Insulation Class	Class II (Double Insulation)
Lid Material	Tinted PC
Material	Halogen-Free Plastic
Mounting Type	Surface
Number of Modules	4
Number of Rows	1
Rated Current	125 A
Rated Impact Resistance	IK08
Rated Voltage	1500 VDC
Standards and Approvals	IEC 62208, Directive 2014/35/EU, AS/NZS 61439.3:2016 Appendix ZZ Clauses 10.101 and 10.102, AS/NZS 3000 Clause 2.10.4.2, IEC 62208 Directive 2014 35/EU Compliant
Weight	0.74 kg
Width	166 mm
Window Type	Transparent
Width(mm)	166

Height(mm) 231

Depth(mm) 113

Drawing

