

Single phase 32A switched socket

Part Numbers

Part Number	Description
W66SS332	32A 3 pin switch socket

Specification

Housing

IP	66
Colour	Light grey
Material - top	Polycarbonate
Material - back box	Polycarbonate
UV stabilised	Yes
Fixing screws	Stainless steel * 8
Gland size & qty	2*M25 + 1*M32

Switch Mechanism

Current rating	32A
Switching poles	3
Rotation	90 deg
Voltage rating	500V AC
Terminal type	1 screw tunnel
Terminal diameter	7.4mm
Terminal depth	17mm
Maximum cable size	16mm ²
Test Standard	IEC947-3/AS3133
M rating (AS3133)	M100
Padlockable	Yes (7mm app)

Socket

Current rating	32A
Phases	1
For pin configuration	3 round pins
Voltage rating	250V AC
Terminal type	Brass - 2 screw
Terminal diameter	5.7mm
Terminal depth	16mm
Maximum cable size	16mm ²
Test Standard	AS3123

Dimensions

Height (ex gland plugs)	197mm
Width	101mm
Depth - top of cover	91mm
Depth - top of handle	110mm



Approval/Compliance certification

Component compliance	Energy safe Vic.
----------------------	------------------

For use with straight plug tops

W66SS332	use W66SP332
----------	--------------

Accessories included

Gland adapters	2
Base screw covers	4
Top screw covers	8 (loose) + 4 (spares)

Spare Components

Back box	W66B2
Isolator	W66IS332LB
Socket 32A 5 pin	W66US332