



Data subject to change without notice. Always confirm the data is correct from the seller.

# KEA 3125 A4

## KEA Aluminium 16-250A

- IP66; Enclosure types A2, A4
- IP65; Enclosure types A5, A6
- IK08; A2, A4 (Degree of mechanical impact)
- IK10: A5, A6
- Excellent for hard weather conditions
- Wide operating temperature range
- Good resistance against many chemicals
- Good UV resistance
- Padlockable
- Door interlock with defeat mechanism
- Tested according to IEC 60947-3
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

**Technical datasheet >>**

Accessories



## Product details

|                                                                             |                   |
|-----------------------------------------------------------------------------|-------------------|
| <b>SKU</b>                                                                  | KEA 3125 A4       |
| <b>AC-21 400/415 V (A)</b>                                                  | 160 A             |
| <b>AC-21 690 V (A)</b>                                                      | 160 A             |
| <b>AC-22 400/415 V (A)</b>                                                  | 125 A             |
| <b>AC-22 690 V (A)</b>                                                      | 125 A             |
| <b>AC-23 400/415 V (A/kW)</b>                                               | 125 A / 55 kW     |
| <b>AC-23 690 V (A/kW)</b>                                                   | 80 A / 75 kW      |
| <b>Cable Area to Switch Terminal (only Cu) (mm<sup>2</sup>) / Bolt size</b> | 6-70              |
| <b>Color</b>                                                                | Standard          |
| <b>EAN</b>                                                                  | 6419410329641     |
| <b>Enclosure</b>                                                            | A4                |
| <b>Enclosure Type</b>                                                       | Aluminium         |
| <b>IP Rating</b>                                                            | 66                |
| <b>Number of Poles</b>                                                      | 3                 |
| <b>Operation</b>                                                            | Front-operated    |
| <b>Switch type</b>                                                          | Load Break Switch |
| <b>Weight (kg)</b>                                                          | 3.5               |

## Dimensional drawing

