



Data subject to change without notice. Always confirm the data is correct from the seller.

KEM 325 M2EMC 2XM25MEMC

EMC Switches 10-630A

- Electromagnetic compatibility ensures safe operation in environments with electromagnetic disturbance
- Tested according to EMC EN 61000-6-3:2007+A1(2011) with EMC-glands shielded power cable
- IP66; Enclosure types U2, U3, A2, A3
- IP65; Enclosure types TR02, TR03, TR04
- Available in polycarbonate up to 125 A, aluminium up to 160 A and sheet steel up to 630 A
- Also available in TR02, TR03 and TR04 enclosures
- Padlockable
- EMC cable glands included
- Door interlock with defeat mechanism
- Tested according to IEC 60947-3
- Also available with 4, 6 or 8-poles
- **Note!** AI-cables cannot be connected directly to switch terminals. For AI-cable connection please use a bi-metal cable connector, **available here**.

Technical datasheet >>

Accessories



Product details

SKU	KEM 325 M2EMC 2XM25MEMC
AC-21 400/415 V (A)	40 A
AC-21 690 V (A)	40 A
AC-22 400/415 V (A)	25 A
AC-22 690 V (A)	25 A
AC-23 400/415 V (A/kW)	25 A / 11 kW
AC-23 690 V (A/kW)	25 A / 22 kW
Cable Area to Switch Terminal (mm²) / Bolt size	1.5-16
Cable Gland	2xM25
Color	Standard
EAN	6419410329214
Enclosure	M2
Enclosure Type	Polycarbonate
IP Rating	66
Number of Poles	3
Operation	Front-operated
Switch type	Load Break Switch
Weight (kg)	0.6

Dimensional drawing

