

Catalogue No: **KL2108**

**MOTOR DRIVEN SIREN MONO72 120dB IP65 240VACDC 1800Hz**

Signalling Devices > Sound Indication > Sirens > Wide Area Sirens - Motor Driven > Mono 72



Representative Photo Only  
(actual product may vary based on configuration selections)

Mono 72, Motor driven siren 240VAC/DC, IP65, 1800 Hz, 120dB @ 1 metre

- Motor driven sirens in various frame sizes, mounting, IP and colours to suit your application.
- Options of constant frequency output (900Hz, 1600Hz, 1800Hz) dependent on model, to most effectively overcome background/ambient noise.
- Available in single or three phase with dB output from 103dB to 145dB, ideal for wide area emergency signalling applications.

#### SPECIFICATIONS

Operating Current Type	AC / DC
Operating Voltage	240
Sound Frequency	1800
Sound output	120
Sound Type	Continuous
IP rating	IP65
Material	Aluminium
Operating temperature, min	-30
Operating temperature, max	45

#### REFERENCES

IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Catalogue No: **KL2108**

**MOTOR DRIVEN SIREN MONO72 120dB IP65 240VACDC 1800Hz**

Signalling Devices > Sound Indication > Sirens > Wide Area Sirens - Motor Driven > Mono 72

