



- FEATURES:**
- Non Perishing to rubber
  - Stops galling & binding
  - Di-electric properties to 70kV
  - Food Grade
  - Long-term Biodegradable
  - Non Toxic
  - Non Carcinogenic
  - Non Leaching
  - Acid & Salt Resistant

- PACK SIZES:**
- 250ml Tube [GS\250T]
  - 235ml Tub [GS\0235]
  - 500ml Tub [GS\0500]
  - 1 Litre Pail [GS\0001]
  - 4 Litre Pail [GS\0004]
  - 20 Litre Pail [GS\0020]

**CONTENTS:** Pure industrial grade lanolin

### USES:

- Anti-seize for threaded rod, nuts & bolts
- Assembly lubricant
- Corrosion & moisture proofing for multi-pin connectors
- Prevents galling of stainless steel and aluminium
- Wire rope lubrication and corrosion protection
- Lubricant for rubber hoses, linkages, pivot pins & bushes
- Stops electrolysis due to similar metals
- Belt dressing

### PHYSICAL PROPERTIES:

- Appearance: Light brown coloured solid
- Boiling Point: Approx. >250°C
- Flash Point: >200°C
- Specific Gravity: 0.90 @ 20°C
- Solubility in Water: Insoluble

### STORAGE & TRANSPORT:

- Lanotec Type A Grease is not classified as Dangerous Goods
- No specific storage required

For safe handling of this product, please consult the product material safety data sheet (MSDS)



**NATURALLY BETTER**

[www.lanotec.com.au](http://www.lanotec.com.au) | [www.youtube.com/LanotecAus](http://www.youtube.com/LanotecAus)

Contact Details for further information:

Ph: +61 7 3373 3700 | Fax: +61 7 3373 3777 | E: [info@lanotec.com.au](mailto:info@lanotec.com.au)

Always read entire label before using product

## APPLICATION:

- Smear onto thread and underside of bolt head. Wipe off excess before tensioning.
- Fill one half of electrical plug to create moisture / dust proof barrier before reconnecting electrical connector.
- Smear grease between dissimilar metals before tightening.
- Smear one flange face only for use as a soft seal gasket.
- Smear O-ring or seal with Type A Grease to hold in place during assembly.
- For wire rope: wipe onto wire rope by hand whilst undertaking regular inspection, or use pressurised applicator such as Masto, Viper, or Raptor.
- Apply directly to squealing belt as a belt dressing (softens and moisturises belt).
- Apply via pump or hand to all shafts and pins prone to drying out or seizing.

## REMOVAL:

- If removal of Lanotec Type A Grease is required, Lanotec Citra-Force or Lanotec PowaWash is recommended

## APPROVALS:

- HACCP Australia Food Safety Accreditation Systems - Food Grade Lubricant
- AQIS Acceptance of Chemical Compound for use in Export Meat Establishments - Category 10 Lubricant Type A
- NZFSA Approval Lubricant C12
- Halal Certification Authority Australia - Taher Accreditation

For safe handling of this product, please consult the product material safety data sheet (MSDS)



**NATURALLY BETTER**

[www.lanotec.com.au](http://www.lanotec.com.au) | [www.youtube.com/LanotecAus](http://www.youtube.com/LanotecAus)

Contact Details for further information:

Ph: +61 7 3373 3700 | Fax: +61 7 3373 3777 | E: [info@lanotec.com.au](mailto:info@lanotec.com.au)