

# PRODUCT DATASHEET

## LM-SV Kit 330-865 20 W

VALUE Flex Kit | LED modules for semi-professional applications

---

### AREAS OF APPLICATION

- Shelf and cupboard lighting
- Coving
- Backlighting

---

### PRODUCT BENEFITS

- Consistent white light (Standard Deviation of Color Matching SDCM: < 5)
- Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back

---

### PRODUCT FEATURES

- Available with color temperature: 2,700 K, 4,000 K and 6,500 K
- Color rendering index  $R_a$ : 80
- Lengths per reel: 5 m, smallest cuttable unit: 83 mm
- Lifetime (L70/B50): up to 20,000 h (temperature at  $T_a = 25\text{ °C}$ )
- Luminous flux: up to 330 lm/m



**TECHNICAL DATA**

## Electrical data

|                        |         |
|------------------------|---------|
| <b>Rated wattage</b>   | 20.00 W |
| <b>Nominal wattage</b> | 20.00 W |
| <b>Nominal voltage</b> | 12.00 V |
| <b>Type of current</b> | DC      |

## Photometrical data

|                                  |          |
|----------------------------------|----------|
| <b>Color temperature</b>         | 6500 K   |
| <b>Light color (designation)</b> | Daylight |
| <b>Luminous flux</b>             | 330 lm   |
| <b>Luminous efficacy</b>         | 16 lm/W  |
| <b>Color rendering index Ra</b>  | 80       |

## Dimensions &amp; weight

|                       |          |
|-----------------------|----------|
| <b>Length</b>         | 5000 mm  |
| <b>Width</b>          | 8.30 mm  |
| <b>Height</b>         | 2.50 mm  |
| <b>Product weight</b> | 250.00 g |

## Temperatures &amp; operating conditions

|                                       |             |
|---------------------------------------|-------------|
| <b>Temperature range in operation</b> | -10...45 °C |
|---------------------------------------|-------------|

## Capabilities

|                 |    |
|-----------------|----|
| <b>Dimmable</b> | No |
|-----------------|----|

## Certificates &amp; standards

|                                |      |
|--------------------------------|------|
| <b>Energy efficiency class</b> | A    |
| <b>Type of protection</b>      | IP44 |

## Logistical data

|                                     |             |
|-------------------------------------|-------------|
| <b>Temperature range at storage</b> | -20...60 °C |
|-------------------------------------|-------------|

**EQUIPMENT / ACCESSORIES**

- LED driver included

**LOGISTICAL DATA**

| Product code  | Product description    | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume                | Gross weight |
|---------------|------------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4058075033559 | LM-SV Kit 330-865 20 W | Shipping carton box<br>10    | 465 mm x 210 mm x 215 mm             | 20.99 dm <sup>3</sup> | 4299.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.