

PRODUCT FAMILY DATASHEET

LED VALUE Tri-Colour Oyster Light

LED ceiling luminaires with three settable color temperatures



AREAS OF APPLICATION

- Living areas (living rooms, dining rooms, bedrooms etc.)

PRODUCT BENEFITS

- Easy and quick installation
- Slim and sleek design

PRODUCT FEATURES

- Three light colors selectable via slide switch
- Lifetime (L70/B50): up to 30,000 h
- Beam angle: 120°
- Type of protection: IP20



TECHNICAL DATA

Product description	Electrical data			Photometrical data		Dimensions & weight			Colors & materials		
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Diameter	Height	Product weight	Body material	Housing color	Product color
VALUE CEILING 13 W 3000 K 4000 5000	13.00 W	220...240 V	50/60 Hz	3000/4000/5000 K	1040/1235 lm	250.0 mm	88.0 mm	310.00 g	Steel	White	White
VALUE CEILING 15 W 3000 K 4000 5000	15.00 W	220...240 V	50/60 Hz	3000/4000/5000 K	1175/1425 lm	300.0 mm	105.0 mm	430.00 g	Steel	White	White
VALUE CEILING 18 W 3000 K 4000 5000	18.00 W	220...240 V	50/60 Hz	3000/4000/5000 K	1440/1620 lm	350.0 mm	110.0 mm	530.00 g	Steel	White	White
VALUE CEILING 24 W 3000 K 4000 5000	24.00 W	220...240 V	50/60 Hz	3000/4000/5000 K	1920/2160 lm	400.0 mm	120.0 mm	680.00 g	Steel	White	White

Product description	Cover material	Temperatures & operating conditions	Lifespan	Capabilities	Certificates & standards	
		Ambient temperature range	Number of switching cycles	Dimmable	Protection class	Type of protection
VALUE CEILING 13 W 3000 K 4000 5000	Polymethylmethacrylate (PMMA)	-20...+40 °C	30000	No	I	IP20
VALUE CEILING 15 W 3000 K 4000 5000	Polymethylmethacrylate (PMMA)	-20...+40 °C	30000	No	I	IP20
VALUE CEILING 18 W 3000 K 4000 5000	Polymethylmethacrylate (PMMA)	-20...+40 °C	30000	No	I	IP20
VALUE CEILING 24 W 3000 K 4000 5000	Polymethylmethacrylate (PMMA)	-20...+40 °C	30000	No	I	IP20

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075207516	Shipping carton box 5	525 mm x 280 mm x 290 mm	2974.00 g	42.63 dm ³
4058075207530	Shipping carton box 5	600 mm x 330 mm x 340 mm	3894.00 g	67.32 dm ³
4058075207554	Shipping carton box 5	660 mm x 380 mm x 390 mm	4924.00 g	97.81 dm ³
4058075207578	Shipping carton box 5	675 mm x 430 mm x 440 mm	6074.00 g	127.71 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.