



CSB surface mount loadcentre, 8way, white door

- Standard AS/NZS 3439-3
- Suit MOD6 MCBs, RCDs & RCBOs
- IP40 rating
- Split neutral and earth bars rated 100A
- Removable earth and neutral bar
- White or transparent door
- Door hinged at the top
- Supplied complete with busbar comb
- Base (ABS)
- Door (white -ABS), (transparent (polycarbonate)
- 8way- Neutral split 4/4 & 8way earth, 12way- Neutral split 5/3/3 & 12way earth
- 18way- Neutral split 9/3/3/3 & 18way earth, 24way- Neutral split 10/3/3/3/3 & 24way earth
- 36way- Neutral split 12/12/12 & 36way earth

Representative Photo Only  
(actual product may vary based on configuration selections)

**SPECIFICATIONS**

Component Type	Power Distribution & Protection	Loadcentre Enclosure
Item Description		CSB surface mount loadcentre, 8way, white door
IP rating		IP40
Number of Poles		8
MCB Type		DIN Profile
Material, body / housing		ABS (Acrylonitrile Butadiene Styrene)
Colour, body / housing		White
Colour, door		White
Ue, rated operational voltage, AC, 3ph, nom		415
Ue, rated operational voltage, AC, 1ph, nom		240
In, rated current		100
In, rated current, busbar comb, centre feed		130
In, rated current, busbar comb, end feed		80
Mounting		Surface Mount
Height		200
Width		185
Depth		94
zzzEarth and Neutral bar Rating		100A 16 mm tunnel terminals
Standards Compliance		AS/NZS 3439.3

Catalogue No: **CSB08SW**

**LOADCENTRE 8 WAY DIN SURFACE WHITE DOOR**

Power Distribution and Protection > Distribution Boards > Loadcentre Assemblies > MOD6 Range of Loadcentres > MOD6 CSB Loadcentres > Insulated Surface Mount White Door



**REFERENCES**

IECEX Certificate -

Supplier Declaration of  
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue  
& Product Selection: -