PVC Control Multicore

CU CNTRL 2.5+E X 12

Contact
OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

Nexans ref.: BFAP07AA012CXWW
GTIN: 9319215383070

12X2.5mm2 + E PVC Control Cable

DESCRIPTION

- Multicore circular+earth,
- 0.6/1kV
- V-90 insulated,
- PVC sheathed to AS/NZS 5000.1,
- Copper conductors, 90°C.

Control Cable

STANDARDS

National AS/NZS 1125; AS/NZS 5000.1

Rated Voltage Uo/U (Um)
0.6/1 kV

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

PVC Control Multicore

CU CNTRL 2.5+E X 12

Contact
OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

CHARACTERISTICS

Construction characteristics	
With Green/Yellow core	Yes
Colour	Black
Outer sheath	PVC
Insulation	V-90
Dimensional characteristics	
Number of earth cores	1
Conductor cross-section	2.5 mm²
Number of cores	12
Nominal overall diameter	19.0 mm
Approximate weight	57.0 kg/100m
Electrical characteristics	
Inductive reactance at 50Hz	0.102 Ohm/km
Max. DC resistance of the conductor at 20°C	7.41 Ohm/km
Conductor AC resistance at 50 Hz	9.45 Ohm/km
Insulation resistance at 20°C	14.0 MOhm.km
Rated Voltage Uo/U (Um)	0.6/1 kV

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.