

PVC Control Multicore

CU CNTRL 2.5+E X 10

Contact

OLEX CUSTOMER SERVICE - Purchase
orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

Nexans ref.: BFAP07AA010CXWW

GTIN: 9319215382998

10X2.5mm² + E PVC Control Cable

DESCRIPTION

- Multicore circular+earth,
- 0.6/1kV
- V-90 insulated,
- PVC sheathed to AS/NZS 5000.1,
- Copper conductors, 90°C.

Control Cable



STANDARDS

National AS/NZS 1125; AS/
NZS 5000.1



Rated Voltage U_o/U (Um)
0.6/1 kV

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 10/12/20 www.olex.com.au Page 1 / 2

PVC Control Multicore

CU CNTRL 2.5+E X 10

Contact

OLEX CUSTOMER SERVICE - Purchase
orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

CHARACTERISTICS

Construction characteristics

With Green/Yellow core	Yes
Colour	Black
Outer sheath	PVC
Insulation	V-90

Dimensional characteristics

Number of earth cores	1
Conductor cross-section	2.5 mm ²
Number of cores	10
Nominal overall diameter	18.1 mm
Approximate weight	50.0 kg/100m

Electrical characteristics

Inductive reactance at 50Hz	0.102 Ohm/km
Max. DC resistance of the conductor at 20°C	7.41 Ohm/km
Conductor AC resistance at 50 Hz	9.45 Ohm/km
Insulation resistance at 20°C	14.0 MOhm.km
Rated Voltage U _o /U (U _m)	0.6/1 kV