

PVC SWA Circular 2C+E & 3C+E

CU ARMAINS 3X 16+6E OG

Contact

OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

Nexans ref.: FNMP15AA003OMAA

GTIN: 9319215059586

3X16mm² + E PVC SWA Circular Orange

DESCRIPTION

- 2 & 3 core+earth,
- Circular,
- 0.6/1kV
- V-90 insulated,
- PVC bedded,
- Steel wire armoured,
- PVC sheathed cable to AS/NZS 5000.1,
- Copper conductors, 90°C.

Orange Circulars; Armoured;



STANDARDS

National AS/NZS 1125; AS/
NZS 5000.1



Rated Voltage U_o/U (Um)
0.6/1 kV



Cable flexibility
Rigid

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 11/12/20 www.olex.com.au Page 1 / 2

PVC SWA Circular 2C+E & 3C+E

CU ARMAINS 3X 16+6E OG

Contact

OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Type of conductor	Stranded copper
With Green/Yellow core	Yes
Insulation	V-90
Armour type	Steel wires
Outer sheath	PVC
Colour	Orange
With smaller neutral conductor	No

Dimensional characteristics

Conductor cross-section	16 mm ²
Number of cores	3
Earth conductor cross section	6 mm ²
Number of earth cores	1
Nominal overall diameter	24.9 mm
Nominal insulation thickness	1.0 mm
Nominal diameter over bedding	18.0 mm
Diameter over armour	21.2 mm
Approximate weight	140.0 kg/100m

Electrical characteristics

Inductive reactance at 50Hz	0.0861 Ohm/km
Max. DC resistance of the conductor at 20°C	1.15 Ohm/km
Conductor AC resistance at 50 Hz	1.47 Ohm/km
Insulation resistance at 20°C	8.4 MOhm.km
Rated Voltage U ₀ /U (Um)	0.6/1 kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

SELLING INFORMATION

Other colours are available on request.