

PVC SWA Circular 4C+E

CU ARMAINS-AUS 4X 1.5+E OG

Contact

OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

Nexans ref.: [HNMP05AA004OMAA](#)

GTIN: 9319215070376

4X1.5mm² + E PVC SWA Circular Orange

DESCRIPTION

- 4 core + earth,
- Circular,
- 0.6/1kV
- V-90 insulated,
- PVC bedded,
- Steel wire armoured,
- PVC sheathed cable to AS/NZS 5000.1,
- Copper conductors, 90°C.

Note: 3½ core (3 core+reduced neutral with or without earth) available on request subject to minimum production runs.



STANDARDS

National AS/NZS 1125; AS/NZS 5000.1



Rated Voltage Uo/U (Um)
0.6/1 kV



Cable flexibility
Rigid

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 11/12/20 www.olex.com.au Page 1 / 2

PVC SWA Circular 4C+E

CU ARMAINS-AUS 4X 1.5+E OG

Contact

OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries
Phone: 1300 CABLES
olex.customerservice@nexans.com

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
With Green/Yellow core	Yes
Outer sheath	PVC
Colour	Orange
Armour type	Steel wires
Material of bedding	PVC filler
Type of conductor	Stranded copper
With smaller neutral conductor	No
Insulation	V-90

Dimensional characteristics

Nominal insulation thickness	0.8 mm
Number of earth cores	1
Conductor cross-section	1.5 mm ²
Earth conductor cross section	1.5 mm ²
Number of cores	4
Nominal diameter over bedding	10.4 mm
Diameter over armour	12.2 mm
Nominal overall diameter	15.9 mm
Approximate weight	46.0 kg/100m

Electrical characteristics

Inductive reactance at 50Hz	0.111 Ohm/km
Max. DC resistance of the conductor at 20°C	13.6 Ohm/km
Insulation resistance at 20°C	17.0 MOhm.km
Conductor AC resistance at 50 Hz	17.3 Ohm/km
Rated Voltage U _o /U (Um)	0.6/1 kV

Mechanical characteristics

Cable flexibility	Rigid
-------------------	-------

SELLING INFORMATION

Other colours are available on request