


2x4mm² 1500V DC Cable

SE017DA, SE017DB

DATA SHEET



Standard
IEC 62930
Type
SOLARTWIN 62930 IEC 131 2X4.0mm ²
Product Application
Connection for solar system



Cable Construction		
Conductor	Construction Item (mm ²)	4.0mm ²
	Construction (mm)	52/0.3±0.008
	Material	Stranded Tinned Copper
	O.D (mm)	2.46
Inner Layer	Material	XLPE
	Color	Black, Red
Outer Layer	Material	XLPE
	Avg.Thick (mm)	0.80
	Min.Thick (mm)	0.58
	O.D (mm)	5.50±0.20 x 11.20±0.30
	Color	Black

Electrical Properties	
Voltage rating	1500V
Dielectric-withstand test	6500VAC/5min
Conductor resistance Max at 20°C	≤5.09Ω/km

Physical Properties	
Elongation of unaged values	≥125%
Tensile strength of unaged values	≥8Mpa
Temperature rating	-40°C to 90°C

Marking
(+) POLE PGK DISTRIBUTION  62930 IEC 131 4mm ² HALOGEN FREE LOW SMOKE 1.5KVDC FOR DC USE ONLY — DO NOT DISCONNECT UNDER LOAD — 90°C SOLAR DC CABLE (+) POLE (This is to be printed on red core of parallel cable)
The marking content of the other side is: (-) POLE PGK DISTRIBUTION  62930 IEC 131 4mm ² HALOGEN FREE LOW SMOKE 1.5KVDC FOR DC USE ONLY — DO NOT DISCONNECT UNDER LOAD — 90°C SOLAR DC CABLE (-) POLE (This is to be printed on black core of parallel cable)

Please Note:

Please consult with your Electrician/Engineer to ensure suitability for the intended application and installation.

PGK Distribution takes every precaution to ensure the information in this publication is correct but accepts no liability of any kind and reserves the right to change any detail in this catalogue without notification.