

## BWP ECO LED WEATHERPROOF BATTEN GEN 2

The high output LED weatherproof batten has longer life and the ability to select your preferred lumen output/wattage within one light fitting.




- Wide Polycarbonate body to cover old footprint
- Robust and lockable stainless steel clips on body
- Easy installation with large terminal block, stainless steel mounting clips, 20mm cable gland and one optional knock-out at the opposite end

LUMEN<sup>SELECT</sup> | COLOUR<sup>SELECT</sup>

80	IP65	IK08	0 - 40°C	Non - Dimmable	54,000hrs (L70/B50)	3 Years	100°
CRI	Ingress Protection Rating	Impact Rating	Operating Temperature	Dimming	Lifetime	Warranty	Beam Angle

CODE	SYSTEM POWER	EXIT LUMEN	LM/W	CCT	DIMENSIONS	WEIGHT	INRUSH CURRENT	LINE CURRENT	
BWPECO202ECS	18W	2100lm	116lm/W	3000K	L655 x W130 x H92mm	1kg	10A	0.08A	
		2500lm	138lm/W	4000K					
		2100lm	116lm/W	6000K					
BWPECO404ECSLS	40W	5200lm	117lm/W	3000K	L1265 x W130 x H92mm	2kg	12A	0.19A	
		33W	4200lm	118lm/W					4000K
		27W	3400lm	133lm/W					6000K
		20W	2500lm	125lm/W					
BWPECO505ECS	52W	5900lm	113lm/W	3000K	L1565 x W130 x H92mm	2kg	13A	0.24A	
		6200lm	119lm/W	4000K					
		5700lm	109lm/W	6000K					



BWPECO202ECS



BWPECO404ECSLS



BWPECO505ECS

Product Images

---



BWPECO404ECSLS



BWPECO505ECS